

Mercury Vapor Standard

H37KC-250/DX FULL CT 12PK

Mercury Vapor lamps feature low initial cost, but have higher operating costs than HPS or Metal Halide due to its lower efficiency. The clear mercury bulb has a bluish green appearance and the Deluxe White has a higher color rendering. Mercury lamps get dimmer over time and rarely burn out, so it is wise to replace them and restore light level.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope ot the lamp is broken or puntured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precuations are used. Certain lamps that will automaticallly extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data

General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	15,000 hour(s)

Light Technical	
Color Code	542 [CCT of 4200K]
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	380
Chromaticity Coordinate Y (Nom)	385
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	48 lm/W

Operating and Electrical	
Power Consumption	250.0 W
Voltage (Nom)	135 V
Voltage (Nom)	135 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Coated glass
Bulb Material	Hard Glass
Bulb Shape	ED90 [ED 90mm]


Mercury Vapor Standard

Approval and Application	
Mercury (Hg) Content (Nom)	38 mg

Product Data	
Order product name	HPL-N 250W E39/41 HG.SLV/12
Full product name	H37KC-250/DX FULL CT 12PK
Order code	248146


Material Nr. (12NC)	928485100091
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677248147
Numerator - Packs per outer box	12
EAN/UPC - Case	50046677248142

Dimensional drawing





Product	D (max)	C (max)
HPL-N 250W E39/41 HG.SLV/12	91 mm	211 mm

Photometric data




Light Distribution Diagram - HPL-N 250W E39/41 HG.SLV/12






Spectral Power Distribution Colour - HPL-N 250W E39/41 HG.SLV/12

Lifetime



Life Expectancy Diagram - HPL-N 250W E39/41 HG.SLV/12



Lumen Maintenance Diagram - HPL-N 250W E39/41 HG.SLV/12

Mercury Vapor Standard



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2023, April 29 - data subject to change