



SON-T

SON-T 100W E E40 1SL/12

High Pressure Sodium lamp with clear tubular outer bulb

Warnings and Safety

- · Control gear must include end-of-life protection (IEC60662, IEC 62035)
- · Control gear must include end-of-life protection (IEC60662, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	E40 [E40]			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Life to 50% Failures (Nom)	28,000 hour(s)			
Light Technical				
Color Code	220 [CCT of 2000K]			
Luminous Flux	9,600 lm			
Correlated Color Temperature (Nom)	2000 K			
Luminous Efficacy (rated) (Nom)	95 lm/W			
Color rendering index (CRI)	-			
Operating and Electrical				
Power Consumption	101 W			
Voltage (Nom)	100 V			

Voltage (Nom)	100 V			
Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb Finish	Clear			
Bulb Shape	T46 [T 46mm]			
Approval and Application				
Mercury (Hg) Content (Nom)	20.2 mg			
Energy Consumption kWh/1000 h	110 kWh			
Product Data				
Order product name	SON-T 100W E E40 1SL/12			
Full product name	SON-T 100W E E40 1SL/12			


Datasheet, 2023, April 14 data subject to change

SON-T

Full product code	692234199954300		
Order code	928494709291		
Material Nr. (12NC)	928494709291		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	6922341999543		


Numerator - Packs per outer box	12
EAN/UPC - Case	6922341993152


Dimensional drawing




Product	D (max)	0	L	C (max)
SON-T 100W E E40 1SL/12	44 mm	47 mm	132 mm	209 mm

Photometric data









Light Distribution Diagram - SON-T 100W E E40 1SL/12

Spectral Power Distribution Colour - SON-T 100W E E40 1SL/12

Lifetime





Life Expectancy Diagram - SON-T 100W E E40 1SL/12

Lumen Maintenance Diagram - SON-T 100W E E40 1SL/12

SON-T



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.