# **PHILIPS** Lighting



# **Ceramalux ALTO**

## SON 250W E39 ED58 CL SLV/12

These lamps pass the EPA's TCLP test for non-hazardous materials. Ideal for industrial applications, warehouses, post top applications and parking lots.

#### **Product data**

General Information		
Cap-Base	E39 [Single Contact Mogul Screw]	
Operating Position	UNIVERSAL [Any or Universal (U)]	
Features	ALTO® (ALTO)	
Light Technical		
Chromaticity Coordinate X (Nom)	523	
Chromaticity Coordinate Y (Nom)	412	
Correlated Color Temperature (Nom)	2100 K	
Luminous Efficacy (Rated) (Min)	102 lm/W	
Luminous Efficacy (rated) (Nom)	114 lm/W	
Color rendering index (CRI)	26	
Operating and Electrical		
Power Consumption	251 W	
Lamp Current (Nom)	3.0 A	
Voltage (Nom)	95 V	
Voltage (Nom)	95 V	

Mechanical and Housing		
Bulb Finish	Clear	
Bulb Material	Hard Glass	
Bulb Shape	ED18	
Approval and Application		
Mercury (Hg) Content (Max)	23.5 mg	
Product Data		
Order product name	SON 250W E39 ED58 CL SLV/12	
Full product name	SON 250W E39 ED58 CL SLV/12	
Order code	928601139401	
Material Nr. (12NC)	928601139401	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	046677368791	
Numerator - Packs per outer box	12	
EAN/UPC - Case	50046677368796	

### Ceramalux ALTO

#### Dimensional drawing

Product	D	C (max)
SON 250W E39 ED58 CL SLV/12	57.2 mm	248 mm





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 4 - data subject to change