

Ceramalux Non-ALTO

70W BD17 HP SODIUM HID CLR

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]

Light Technical	
Chromaticity Coordinate X (Nom)	522
Chromaticity Coordinate Y (Nom)	425
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (Rated) (Min)	84 lm/W
Luminous Efficacy (rated) (Nom)	93 lm/W
Color rendering index (CRI)	13

Operating and Electrical	
Power Consumption	70.2 W
Lamp Current (Nom)	1.6 A
Voltage (Nom)	52 V
Voltage (Nom)	52 V

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Soft Glass
Bulb Shape	BD17


Approval and Application	
Mercury (Hg) Content (Max)	17 mg

Product Data	
Order product name	70W BD17 HP SODIUM HID CLR
Full product name	70W BD17 HP SODIUM HID CLR
Order code	928601144114
Material Nr. (12NC)	928601144114
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677460815
Numerator - Packs per outer box	3
EAN/UPC - Case	50046677460810

Ceramalux Non-ALTO

Dimensional drawing

Product	D	C (max)
70W BD17 HP SODIUM HID CLR	55 mm	138 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.