



Ceramalux Non-ALTO

SON 70W E26 BD54 CO SLV/12

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]
Light Technical	
Chromaticity Coordinate X (Nom)	522
Chromaticity Coordinate Y (Nom)	425
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (Rated) (Min)	78 lm/W
Luminous Efficacy (rated) (Nom)	87 lm/W
Color rendering index (CRI)	13
Operating and Electrical	
Lamp Current (Nom)	1.6 A
Voltage (Nom)	52 V
Voltage (Nom)	52 V
Mechanical and Housing	
Bulb Finish	Coated glass

Bulb Material	Hard Glass
Bulb Shape	BD17
Approval and Application	
Mercury (Hg) Content (Max)	17 mg
Product Data	
Order product name	SON 70W E26 BD54 CO SLV/12
Full product name	SON 70W E26 BD54 CO SLV/12
Order code	928601144201
Material Nr. (12NC)	928601144201
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677332143
Numerator - Packs per outer box	12
EAN/UPC - Case	50046677332148

Ceramalux Non-ALTO

Dimensional drawing

Product	D	C (max)
SON 70W E26 BD54 CO SLV/12	2.125 inch	5.438 inch

