

Ceramalux ALTO Non-Cycling

C150S55/ALTO NC HPS 12PK

Philips Ceramalux High Pressure Sodium Non-Cycling Lamps are a better value than standard high pressure sodium lamps, with longer life and reduced maintenance cost.

Product data

General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]
Features	ALTO® Non-Cycling

Light Technical	
Chromaticity Coordinate X (Nom)	0.525
Chromaticity Coordinate Y (Nom)	0.417
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (Rated) (Min)	96 lm/W
Luminous Efficacy (rated) (Nom)	106 lm/W
Color rendering index (CRI)	21

Operating and Electrical	
Power Consumption	150.6 W
Lamp Current (Nom)	3.2 A
Voltage (Nom)	55 V
Voltage (Nom)	55 V


Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	ED-23 1/2

Approval and Application	
Mercury (Hg) Content (Nom)	2 mg

Product Data	
Order product name	C150S55/ALTO NC HPS 12PK
Full product name	C150S55/ALTO NC HPS 12PK
Order code	147413
Material Nr. (12NC)	928601156002
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677147419
Numerator - Packs per outer box	12
EAN/UPC - Case	50046677147414

Ceramalux ALTO Non-Cycling

Dimensional drawing



Product	D	L	C (max)
C150S55/ALTO NC HPS 12PK	2.94 inch	5.000 inch	7.75 inch

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.