



MASTERColour CDM-T Elite MW

MASTERC CDM-TMW Elite 210W/942 1CT/12

The medium wattage lighting system that gives superior, longer-lasting white light for both indoor and outdoor use

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing, except for protected versions with PGZX18 cap, which are designed for open luminaires (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	PGZ18
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	30,000 hour(s)
Light Technical	
Color Code	942 [CCT of 4200K]
Color Designation	Cool White (CW)
Saturated Red (R9)	80
Chromaticity Coordinate X (Nom)	0.381
Chromaticity Coordinate Y (Nom)	0.374
Correlated Color Temperature (Nom)	3960 K
Luminous Efficacy (Rated) (Min)	98 lm/W


Luminous Efficacy (rated) (Nom)	108 lm/W
Color rendering index (CRI)	92
Operating and Electrical	
Power Consumption	210.0 W
Voltage (Nom)	98 V
Voltage (Nom)	98 V
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	TMW28

MASTERC colour CDM-T Elite MW

Approval and Application	
Mercury (Hg) Content (Max)	25 mg
Energy Consumption kWh/1000 h	231 kWh
Product Data	
Order product name	MASTERC CDM-TMW Elite 210W/942 1CT/12
Full product name	MASTERC CDM-TMW Elite 210W/942 1CT/12
Full product code	692234199996300


Order code	928601164934
Material Nr. (12NC)	928601164934
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6922341999963
Numerator - Packs per outer box	12
EAN/UPC - Case	6922341993572

Dimensional drawing




Product	D (max)	D	D	C (max)	C
MASTERC CDM-TMW Elite 210W/942 1CT/12	29 mm	1.1 inch	28 mm	188 mm	186 mm

Photometric data




Light Distribution Diagram - MASTERC CDM-TMW Elite 210W/942 1CT/12




Spectral Power Distribution Colour - MASTERC CDM-TMW Elite 210W/942 1CT/12

MASTERC colour CDM-T Elite MW

Lifetime



Life Expectancy Diagram - MASTERC CDM-TM Elite 210W/942 1CT/12



Lumen Maintenance Diagram - MASTERC CDM-TM Elite 210W/942 1CT/12

