



# MASTERColour CDM-T Elite MW



## CDM Elite TMW 315/942/U/O EU

The medium wattage lighting system that gives superior, longer-lasting white light for both indoor and outdoor use

#### **Warnings and Safety**

- Use only in totally enclosed luminaire, even during testing, except for protected versions with PGZX18 cap, which are designed for open luminaires (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$  The luminaire must be able to contain hot lamp parts if the lamp ruptures
- $\boldsymbol{\cdot}$  Use only with electronic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information			
Cap-Base	PGZX18		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Features	Protected (P)		
Flux measurement reference	Sphere		
Life to 50% Failures (Nom)	30,000 hour(s)		
Light Technical			
Color Code	942 [CCT of 4200K]		
Luminous Flux	34,300 lm		
Color Designation	Cool White (CW)		
Saturated Red (R9)	50		
Chromaticity Coordinate X (Nom)	0.371		

Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (Rated) (Min)	99 lm/W
Luminous Efficacy (rated) (Nom)	109 lm/W
Color rendering index (CRI)	93
Arc Length O (Nom)	14 mm
Operating and Electrical	
Power Consumption	315.9 W
Voltage (Nom)	100 V
Voltage (Nom)	100 V


Datasheet, 2024, February 8 data subject to change

## MASTERColour CDM-T Elite MW

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T12
Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) Content (Max)	25 mg
Energy Consumption kWh/1000 h	316 kWh
EPREL Registration Number	473302
	-


Product Data			
Order product name	CDM Elite TMW 315/942/U/O EU		
Full product name	CDM Elite TMW 315/942/U/O EU		
Full product code	871829113960700		
Order code	928601167331		
Material Nr. (12NC)	928601167331		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8727900862157		
Numerator - Packs per outer box	12		
EAN/UPC - Case	8718291139614		


### Dimensional drawing




Product	D	D	С
CDM Elite TMW 315/942/U/O EU	1.5 inch	38 mm	193 mm

### Photometric data









Light Distribution Diagram - CDM Elite TMW 315/942/U/O EU

Spectral Power Distribution Colour - CDM Elite TMW 315/942/U/O EU

## **MASTERColour CDM-T Elite MW**

#### Lifetime





Life Expectancy Diagram - CDM Elite TMW 315/942/U/O EU

Lumen Maintenance Diagram - CDM Elite TMW 315/942/U/O EU



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.