



# MASTER Plastic LEDbulbs

#### MAS LEDbulb D 13-75W E27 827 A67

The MASTER Plastic LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to incandescent lamps. They are particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 holder and designed for retrofit replacement of incandescent bulbs, MASTER Plastic LEDbulb delivers huge energy savings of up to 80% compared with traditional incandescent lamps and provides excellent quality of light. By offering a lifetime of 25,000 hours it lowers maintenance costs. They can be used together with most leading-edge dimmers, enabling further efficiencies while helping to create the desired atmosphere.

#### **Warnings and Safety**

- $\cdot$  Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- · Not intended for use with emergency light fixtures or exit lights

#### **Product data**

General Information		
Cap-Base	E27 [E27]	
Nominal lifetime	25,000 hour(s)	
Switching Cycle	50,000	
Lighting Technology	LED	
EU RoHS compliant	Yes	

Light Tashuisal	
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	1,055 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	81.15 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

Datasheet, 2023, December 6 data subject to change

# **MASTER Plastic LEDbulbs**

LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 Hz
Input Frequency	50 Hz
Power Consumption	13 W
Lamp Current (Nom)	62 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Davier Factor (Fraction)	0.5
Power Factor (Fraction)	0.5
Voltage (Nom)	220-240 V
Voltage (Nom)	
Voltage (Nom)  Controls and Dimming	220-240 V
Voltage (Nom)  Controls and Dimming	220-240 V
Voltage (Nom)  Controls and Dimming  Dimmable	220-240 V


Yes
13 kWh
MAS LEDbulb D 13-75W E27 827 A67
MAS LEDbulb D 13-75W E27 827 A67
871829175852500
929000276602
929000276602
1
8718291758525
6
8718291758532

# Dimensional drawing



Product	D	С
MAS LEDbulb D 13-75W E27 827 A67	66 mm	122.6 mm

### Photometric data



Light Distribution Diagram - MAS LEDbulb D 13-75W E27 827 A67

# **MASTER Plastic LEDbulbs**



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.