



MASTER LEDtube EM/ Mains T8

MAS LEDtube STD 1200mm 20W830 T8 I

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance, which cannot be distinguished from traditional fluorescent. These T8 LED tubes are the right choice for absolute performance and are designed to stand up to everyday conditions. Unparalleled savings thanks to low energy consumption and an exceptionally long lifetime ensure this tube masters every demanding application.

Warnings and Safety

- NOTE: The overall energy efficiency and light distribution of any installation that uses these lamps will be determined by the design of the installation.

Product data

General Information		LLMF At End Of Nominal Lifetime (Nom) 70 %	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]		
Nominal lifetime	40,000 hour(s)		
Switching Cycle	50,000		
Lighting Technology	LED		
EU RoHS compliant	Yes		
Light Technical		Operating and Electrical	
Color Code	830 [CCT of 3000K]	Line Frequency	50 to 60 Hz
Beam Angle (Nom)	150 degree(s)	Input Frequency	50 to 60 Hz
Luminous Flux	2,000 lm	Power Consumption	20 W
Correlated Color Temperature (Nom)	3000 K	Starting Time (Nom)	0.5 s
Color Consistency	<6	Warm-up time to 60% light	Instant full light s
Color rendering index (CRI)	83	Power Factor (Fraction)	0.9
		Voltage (Nom)	100-240 V
		Temperature	
		Ambient temperature range	-20 °C to 45 °C

MASTER LEDtube EM/Mains T8


T-Case Maximum (Nom)	55 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	1,200 mm
Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	No
Approval Marks	CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	20 kWh

Product Data	
Order product name	MAS LEDtube STD 1200mm 20W830 T8 I
Full product name	MAS LEDtube STD 1200mm 20W830 T8 I
Full product code	871829173480200
Order code	929000286308
Material Nr. (12NC)	929000286308
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291734802
Numerator - Packs per outer box	10
EAN/UPC - Case	8718291734819


Dimensional drawing

Product	D1	D2	A1	A2	A3
MAS LEDtube STD 1200mm 20W830 T8 I	25.68 mm	28 mm	1,198.0 mm	1,205.0 mm	1,212.0 mm

Photometric data



Light Distribution Diagram - MAS LEDtube STD 1200mm 20W830 T8 I



Spectral Power Distribution Colour - MAS LEDtube STD 1200mm 20W830 T8 I

MASTER LEDtube EM/Mains T8

