



# InteGrade LED fixture system

# InteGrade fixture value 875mm(34") 840

The InteGrade LED fixture system is an energy-efficient way to create an enjoyable shopping experience. Thanks to its compact dimensions, the fixture can be aesthetically integrated below and inside shelves, e.g. in a store interior or refrigerated cabinet. Asymmetrical optics direct the light where you want it, thus making optimum use of the light and energy. The products or background you want lit will be presented uniformly, with reduced glare and dark spots. Our LEDs have minimal output degradation and colour shift, so the light remains consistent throughout their long lifetime. InteGrade LED is an ideal solution for high-quality lighting without flicker or colour differences. The fixture consists of a profile with LED engines and inline locks. Mounting accessories, cables and LED power driver are available separately.

### **Product data**

General Information		
Lighting Technology	LED	
Light Technical		
Color Code	840 [CCT of 4000K]	
Luminous Flux	600 lm	
Life to 70% Lumen Maintenance	50,000 hour(s)	
Color Consistency Initial	5	
Correlated Color Temperature (Nom)	4100 K	
Luminous Efficacy (rated) (Nom)	75 lm/W	
Color rendering index (CRI)	85	

Operating and Electrical			
Power Consumption	8 W		
Temperature			
Ambient temperature range	-30 °C to 30 °C		
Mechanical and Housing			
Product Length	875 mm		
Approval and Application			
Approval Marks	CE marking UL certificate		
Product Data			
Order product name	InteGrade fixture value 875mm(34") 840		


Datasheet, 2023, April 29 data subject to change


# **InteGrade LED fixture system**

Full product name	InteGrade fixture value 875mm(34") 840
Full product code	871829123624500
Order code	929000645713
Material Nr. (12NC)	929000645713
Numerator - Quantity Per Pack	1

EAN/UPC - Product/Case	8718291236245	
Numerator - Packs per outer box	12	
EAN/UPC - Case	8718291236252	

## Dimensional drawing





Product	C (max)	A (max)	B1
InteGrade fixture value 875mm(34") 840	12.0 mm	883.0 mm	23.0 mm

