



LED PAR38

15PAR38/F25 3000 CW SO 6/1

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	50,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	25 degree(s)
Luminous Flux	900 lm
Luminous Intensity (Nom)	4,200 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	64.29 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	14 W
Lamp Current (Nom)	126 mA

Wattage Equivalent	95 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	PAR38 [PAR 4.75 inch/121mm]


Approval and Application	
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	14 kWh

Product Data	
Order product name	120V PAR38 14W 25D 3000K 900 CW SO
Full product name	15PAR38/F25 3000 CW SO 6/1
Order code	434968
Material Nr. (12NC)	929001110404
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677434960
Numerator - Packs per outer box	6

LED PAR38


EAN/UPC - Case	50046677434965
----------------	----------------

Dimensional drawing



Product	D	C
120V PAR38 14W 25D 3000K 900 CW SO	120 mm	131 mm

Photometric data



Light Distribution Diagram - 120V PAR38 14W 25D 3000K 900 CW SO

