PHILIPS Lighting

MASTER LEDtube EM/ Mains T8

MAS LEDtube 1500mm HO 23W840 T8

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. This product is the ideal solution for up lamping in general lighting applications.

Warnings and Safety

• -

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Nominal lifetime	50,000 hour(s)				
Switching Cycle	200,000				
Lighting Technology	LED				
EU RoHS compliant	Yes				
Light Technical					
Color Code	840 [CCT of 4000K]				
Beam Angle (Nom)	160 degree(s)				
Luminous Flux	3,100 lm				
Color Designation	Cool White (CW)				
Correlated Color Temperature (Nom)	4000 K				
Color Consistency	<6				
Color rendering index (CRI)	80				
LLMF At End Of Nominal Lifetime (Nom) 70 %					


Operating and Electrical				
Line Frequency	50 to 60 Hz			
Input Frequency	50 to 60 Hz			
Power Consumption	23 W			
Lamp Current (Max)	105 mA			
Lamp Current (Min)	95 mA			
Starting Time (Nom)	0.5 s			
Warm-up time to 60% light	0.5 s			
Power Factor (Fraction)	0.9			
Voltage (Nom)	220-240 V			
Temperature				
Ambient temperature range	-20 ℃ to 35 ℃			
T-Case Maximum (Nom)	55 ℃			
Controls and Dimming				
Dimmable	No			

MASTER LEDtube EM/Mains T8

Mechanical and Housing				
Product Length	1,500 mm			
Approval and Application				
Energy Saving Product	Yes			
Suitable For Accent Lighting	No			
Approval Marks	CE marking RoHS compliance KEMA Keur			
	certificate			
Energy Consumption kWh/1000 h	23 kWh			
Product Data				
Order product name	MAS LEDtube 1500mm HO 23W840 T8			


Full product name	MAS LEDtube 1500mm HO 23W840 T8			
Full product code	871829178958100			
Order code	929001116102			
Material Nr. (12NC)	929001116102			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8718291789581			
Numerator - Packs per outer box	10			
EAN/UPC - Case	8718291789598			

Dimensional drawing




Product	D1	D2	A1	A2	A3
MAS LEDtube 1500mm HO	25.68 mm	28 mm	1,500.0 mm	1,507.1 mm	1,514.2 mm
23W840 T8					

Photometric data



Light Distribution Diagram - MAS LEDtube 1500mm HO 23W840 T8



Spectral Power Distribution Colour - MAS LEDtube 1500mm HO 23W840 T8

MASTER LEDtube EM/Mains T8



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 29 - data subject to change