

MASTER LEDtube EM/ Mains T8

MAS LEDtube STD 1200mm 20W865 T8 I

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. This product is the ideal solution for up lamping in general lighting applications.

Warnings and Safety

٠ _

Product data

General Information			
Cap-Base	G13 [Medium Bi-Pin Fluorescent]		
Nominal lifetime	40,000 hour(s)		
Switching Cycle	50,000		
Lighting Technology	LED		
EU RoHS compliant	Yes		
Light Technical			
Color Code	865 [CCT of 6500K]		
Beam Angle (Nom)	150 degree(s)		
Luminous Flux	2,100 lm		
Correlated Color Temperature (Nom)	6500 K		
Color Consistency	<6		
Color rendering index (CRI)	83		
LLMF At End Of Nominal Lifetime (Nom) 70 %		
Operating and Electrical			
Line Frequency	50 to 60 Hz		

Input Frequency	50 to 60 Hz			
Power Consumption	20 W			
Starting Time (Nom)	0.5 s			
Warm-up time to 60% light	Instant full light s			
Power Factor (Fraction)	0.9			
Voltage (Nom)	220-240 V			
Temperature				
Ambient temperature range	-20 °C to 45 °C			
T-Case Maximum (Nom)	50 ℃			
Controls and Dimming				
Dimmable	No			
Mechanical and Housing				
Product Length	1,200 mm			


Datasheet, 2023, April 29 data subject to change

MASTER LEDtube EM/Mains T8

Approval and Application				
Energy Saving Product	Yes			
Suitable For Accent Lighting	No			
Approval Marks	CE marking RoHS compliance KEMA Keur			
	certificate			
Energy Consumption kWh/1000 h	20 kWh			
Product Data				
Order product name	MAS LEDtube STD 1200mm 20W865 T8 I			
Full product name	MAS LEDtube STD 1200mm 20W865 T8 I			

Full product code	871869642190100		
Order code	929001127008		
Material Nr. (12NC)	929001127008		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8718696421901		
Numerator - Packs per outer box	10		
EAN/UPC - Case	8718696421918		


Dimensional drawing



Product	D1	D2	A1	A2	А3
MAS LEDtube STD 1200mm	25.68 mm	28 mm	1,198.0 mm	1,205.0 mm	1,212.0 mm
20W865 T8 I					

Photometric data





Light Distribution Diagram - MAS LEDtube STD 1200mm 20W865 T8 I

Spectral Power Distribution Colour - MAS LEDtube STD 1200mm 20W865 T8 I

MASTER LEDtube EM/Mains T8



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.