



MASTER VALUE LEDspot MV

MAS LEDspotMV DimTone 4-35W GU10 25D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiences for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings that normal LED spots.

Warnings and Safety

- · Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	822-827 [tunable warm white]
Beam Angle (Nom)	25 degree(s)
Luminous Flux	305 lm
·	·

Luminous Intensity (Nom)	1,000 cd
Color Designation	Warm White (WW)
Luminous Efficacy (rated) (Nom)	70.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	280 lm
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz


Datasheet, 2023, December 6 data subject to change

MASTER VALUE LEDspot MV

Power Consumption	4 W	
Lamp Current (Nom)	22 mA	
Starting Time (Nom)	0.5 s	
Warm-up time to 60% light	instant full light s	
Power Factor (Fraction)	0.5	
Voltage (Nom)	220-240 V	
Temperature		
T-Case Maximum (Nom)	70 °C	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Bulb Shape	PAR16 [PAR 2 inch/50mm]	

Approval and Application		
Suitable For Accent Lighting	Yes	
Energy Consumption kWh/1000 h	4 kWh	
Product Data		
Order product name	MAS LEDspotMV DimTone 4-35W GU10 25	
Full product name	MAS LEDspotMV DimTone 4-35W GU10 25	
Full product code	871869643828200	
Order code	929001130602	
Material Nr. (12NC)	929001130602	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718696438282	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8718696438299	

Dimensional drawing



Product	D	С
MAS LEDspotMV DimTone 4-35W GU10 25D	50 mm	55 mm

Photometric data



Light Distribution Diagram - MAS LEDspotMV DimTone 4-35W GU10 25D

Spectral Power Distribution Colour - MAS LEDspotMV DimTone 4-35W GU10 25D

MASTER VALUE LEDspot MV



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.