

MASTER Plastic LEDbulbs

MAS LEDbulb D 9-60W E27 827 A60 CL

MASTER LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to the incandescent lamp. It is particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 or a B22 holder and designed for retrofit replacement of incandescent bulbs, MASTER LEDbulb delivers huge energy savings and minimises maintenance cost without any compromise on light quality.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information		Light Technical	
Cap-Base	E27 [E27]	Color Code	827 [CCT of 2700K]
Nominal lifetime	25,000 hour(s)	Luminous Flux	806 lm
Switching Cycle	50,000	Color Designation	Warm White (WW)
Lighting Technology	LED	Correlated Color Temperature (Nom)	2700 K
EU RoHS compliant	Yes	Luminous Efficacy (rated) (Nom)	78.00 lm/W
		Color Consistency	<6

MASTER Plastic LEDbulbs

Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	9 W
Lamp Current (Nom)	51 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	85 °C
----------------------	-------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb Finish	Clear
-------------	-------

Bulb Shape	A60 [A 60mm]
------------	--------------


Approval and Application

Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	6 kWh

Product Data


Order product name	MAS LEDbulb D 9-60W E27 827 A60 CL
Full product name	MAS LEDbulb D 9-60W E27 827 A60 CL
Full product code	871869644647800
Order code	929001134402
Material Nr. (12NC)	929001134402
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696446478
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696446485

Dimensional drawing



Product	D	C
MAS LEDbulb D 9-60W E27 827 A60 CL	60 mm	110 mm

Photometric data



Light Distribution Diagram - MAS LEDbulb D 9-60W E27 827 A60 CL

Spectral Power Distribution Colour - MAS LEDbulb D 9-60W E27 827 A60 CL

MASTER Plastic LEDbulbs

