



MASTER VALUE LEDspot MV

MAS LEDspotMV D 5.4-50W GU10 940 40D

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information		Luminous Intensity (Nom)	
Cap-Base	GU10 [GU10]	830 cd	
Nominal lifetime	50,000 hour(s)	Color Designation	White (WH)
Switching Cycle	50,000	Correlated Color Temperature (Nom)	4000 K
Lighting Technology	LED	Luminous Efficacy (rated) (Nom)	72.59 lm/W
EU RoHS compliant	Yes	Color Consistency	<6
Light Technical		Color rendering index (CRI)	90
Color Code	940 [CCT of 4000K]	LLMF At End Of Nominal Lifetime (Nom)	70 %
Beam Angle (Nom)	40 degree(s)	Luminous Flux in 90° Cone (Rated)	392 lm
Luminous Flux	416 lm	Operating and Electrical	
		Line Frequency	50 to 60 Hz

MASTER VALUE LEDspot MV

Input Frequency	50 to 60 Hz
Power Consumption	5.4 W
Lamp Current (Nom)	28 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	0.85
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	91 °C
----------------------	-------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb Shape	PAR16 [PAR 2 inch/50mm]
------------	-------------------------


Approval and Application

Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	6 kWh

Product Data


Order product name	MAS LEDspotMV D 5.4-50W GU10 940 40D
Full product name	MAS LEDspotMV D 5.4-50W GU10 940 40D
Full product code	871869645725200
Order code	929001139102
Material Nr. (12NC)	929001139102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696457252
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696457269

Dimensional drawing



Product	D	C
MAS LEDspotMV D 5.4-50W GU10 940 40D	50 mm	57 mm

Photometric data



Light Distribution Diagram - MAS LEDspotMV D 5.4-50W GU10 940 40D



Spectral Power Distribution Colour - MAS LEDspotMV D 5.4-50W GU10 940 40D

MASTER VALUE LEDspot MV

