



MASTER VALUE LEDspot MV

MASTER LEDspotMV D 4-35W GU10 940 40D

Delivering a warm, halogen-like accent beam, the MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it achieves more natural colours, creating cosy and comfortable ambience for residential and hospitality projects, and emphasising the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. The MASTER VALUE also offers more energy savings than normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information			
Cap base	GU10 [GU10]	Luminous intensity (nom.)	624 cd
Nominal lifetime	50,000 h	Colour designation	White (WH)
Switching Cycle	50,000	Correlated Colour Temperature	4000 K
Lighting Technology	LED	Luminous efficacy (rated) (nom.)	71.25 lm/W
EU RoHS compliant	Yes	Colour consistency	<6
		Colour rendering index (CRI)	90
		LLMF at end of nominal lifetime (nom.)	70 %
		Luminous flux in 90° cone (rated)	295 lm
Light Technical		Operating and Electrical	
Colour Code	940 [CCT of 4000K]	Line Frequency	50 to 60 Hz
Beam angle (nom.)	40 degree(s)		
Luminous Flux	314 lm		

MASTER VALUE LEDspot MV

Input frequency	50 to 60 Hz
Power Consumption	4 W
Lamp current (nom.)	21 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	0.84
Voltage (nom.)	220-240 V

Temperature

T-Case maximum (nom.)	90 °C
-----------------------	-------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb shape	PAR16 [PAR 2 inch/50 mm]
------------	--------------------------


Approval and Application

Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	4 kWh

Product Data


Order product name	MAS LEDspotMV D 4-35W GU10 940 40D
Full product name	MASTER LEDspotMV D 4-35W GU10 940 40D
Full EOC	871869645739900
Order code	45739900
Material no. (12 NC)	929001139702
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696457399
Numerator – packs per outer box	10
EAN/UPC - Case	8718696457405

Dimensional drawing



Product	D	C
MAS LEDspotMV D 4-35W GU10 940 40D	50 mm	57 mm

Photometric data



Light Distribution Diagram - MAS LEDspotMV D 4-35W GU10 940 40D



Spectral Power Distribution Colour - MAS LEDspotMV D 4-35W GU10 940 40D

MASTER VALUE LEDspot MV

