



MASTER LEDcandle DiamondSpark

MASTER LEDcandle DT 4-25W E14 B38 CL

Delivering incandescent-like sparkling light effects, MASTER LEDcandle bulbs are ideal for general and decorative lighting in the hospitality industry, as well as in home environments. The dimmable MASTER LEDcandles drive further efficiencies, while helping to create the desired atmosphere. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass bulbs fit all existing fixtures with an E14 and B15 socket. Drawing upon inputs from chandelier makers and designed to enhance the aesthetic appeal of the chandelier or luminaire, not only when lit but also when not, these lamps come in a classical slender shape with a unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost. The flame-shaped candle lamps comes in a classical slender shape with a unique, eye-catching lens design that perfectly complements modern LED candles.

Product data

| General Information | |
|----------------------------------|------------------------------|
| Cap base | E14 [E14] |
| Nominal lifetime | 25,000 h |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| EU RoHS compliant | Yes |
| Light Technical | |
| Colour Code | 822-827 [tunable warm white] |
| Luminous Flux | 250 lm |
| Colour designation | Warm White (WW) |
| Luminous efficacy (rated) (nom.) | 65 lm/W |
| Colour consistency | <6 |


| Colour rendering index (CRI) | 80 |
|--|----------------------|
| LLMF at end of nominal lifetime (nom.) | 70 % |
| Operating and Electrical | |
| Line Frequency | 50 to 60 Hz |
| Input frequency | 50 to 60 Hz |
| Power Consumption | 4 W |
| Lamp current (nom.) | 25 mA |
| Wattage equivalent | 25 W |
| Starting time (nom.) | 0.5 s |
| Warm-up time to 60% light | Instant full light s |
| Power Factor (Fraction) | 0.7 |

MASTER LEDcandle DiamondSpark

| | |
|------------------------------------|-----------|
| Voltage (nom.) | 220-240 V |
| Temperature | |
| T-Case maximum (nom.) | 85 °C |
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Lamp Finish | Clear |
| Bulb shape | B38 |
| Approval and Application | |
| Suitable for accent lighting | No |
| Energy consumption kWh/1,000 hours | 4 kWh |


| | |
|-----------------------------------|--------------------------------------|
| EyeComfort | Yes |
| Product Data | |
| Order product name | MAS LEDcandle DT 4-25W E14 B38 CL |
| Full product name | MASTER LEDcandle DT 4-25W E14 B38 CL |
| Full EOC | 871869645368100 |
| Order code | 45368100 |
| Material no. (12 NC) | 929001139802 |
| SAP numerator – quantity per pack | 1 |
| EAN/UPC – Product/Case | 8718696453681 |
| Numerator – packs per outer box | 10 |
| EAN/UPC - Case | 8718696453698 |

Dimensional drawing



| Product | D | C |
|-----------------------------------|-------|--------|
| MAS LEDcandle DT 4-25W E14 B38 CL | 38 mm | 113 mm |

Photometric data



Light Distribution Diagram - MAS LEDcandle DT 4-25W E14 B38 CL

Spectral Power Distribution Colour - MAS LEDcandle DT 4-25W E14 B38 CL

MASTER LEDcandle DiamondSpark

