



MASTER LEDspot PAR

MASTER LEDspot D 5.5-50W 4000K PAR20 25D

With its robust design and warm-white beam of light, these new-generation PAR lamps are ideal for general lighting and spot lighting in the hospitality industry. There is a choice of dimmable and non-dimmable versions. They are especially suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 holder and designed for retrofit replacement of halogen/incandescent lamps, MASTER LEDspot PAR deliver huge energy savings and minimize maintenance cost without any reduction in brightness. The IP44-rated outdoor version of the PAR 38 lamp is one of the few energy-saving alternatives to incandescent PAR38 outdoor lamps available today. The dimmable PAR 20 is a perfect replacement for an incandescent spot.

Product data

| General Information | |
|----------------------------------|--------------------|
| Cap base | E27 [E27] |
| Nominal lifetime | 45,000 h |
| Switching Cycle | 20,000 |
| Lighting Technology | LED |
| EU RoHS compliant | Yes |
| | |
| Light Technical | |
| Colour Code | 840 [CCT of 4000K] |
| Beam angle (nom.) | 25 degree(s) |
| Luminous Flux | 520 lm |
| Luminous intensity (nom.) | 2,150 cd |
| Colour designation | Cool White (CW) |
| Correlated Colour Temperature | 4000 K |
| Luminous efficacy (rated) (nom.) | 94 lm/W |
| Colour consistency | <6 |
| Colour rendering index (CRI) | 80 |
| | |

| LLMF at end of nominal lifetime (nom.) 70 $\%$ | | | |
|--|----------------------|--|--|
| Luminous flux in 90° cone (rated) | 475 lm | | |
| | | | |
| Operating and Electrical | | | |
| Line Frequency | 50 Hz | | |
| Input frequency | 50 Hz | | |
| Power Consumption | 5.5 W | | |
| Lamp current (nom.) | 31 mA | | |
| Starting time (nom.) | 0.5 s | | |
| Warm-up time to 60% light | Instant full light s | | |
| Power Factor (Fraction) | 0.85 | | |
| Voltage (nom.) | 230 V | | |
| | | | |
| Temperature | | | |
| T-Case maximum (nom.) | 85 ℃ | | |
| | | | |


Datasheet, 2023, April 29 data subject to change

MASTER LEDspot PAR

| Controls and Dimming | |
|------------------------------------|--------------------------------------|
| Dimmable | Yes |
| | |
| Mechanical and Housing | |
| Bulb shape | PAR20 [PAR 2.5 inch/63 mm] |
| | |
| Approval and Application | |
| Suitable for accent lighting | Yes |
| Energy consumption kWh/1,000 hours | 6 kWh |
| | |
| Product Data | |
| Order product name | MASTER LEDspot D 5.5-50W 4000K PAR20 |


| Full product name | MASTER LEDspot D 5.5-50W 4000K PAR20 | |
|-----------------------------------|--------------------------------------|--|
| | 25D | |
| Full EOC | 871869646067200 | |
| Order code | 46067200 | |
| Material no. (12 NC) | 929001145502 | |
| Local order code | MLED6PAR204025D | |
| SAP numerator – quantity per pack | 1 | |
| EAN/UPC — Product/Case | 8718696460672 | |
| Numerator – packs per outer box | 6 | |
| EAN/UPC - Case | 8718696460689 | |
| | | |

Dimensional drawing




| Product | D | С |
|--|-------|---------|
| MASTER LEDspot D 5.5-50W 4000K PAR20 25D | 65 mm | 85.2 mm |

Photometric data



Light Distribution Diagram - MASTER LEDspot D 5.5-50W 4000K PAR20 25D



Spectral Power Distribution Colour - MASTER LEDspot D 5.5-50W 4000K PAR20 25D

MASTER LEDspot PAR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.