

LED InstantFit Lamps

10.5PL-C/T LED/26V-3500 IF 4P 10/1

Philips LED T8 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

Warnings and Safety

- Perform a visual inspection to ensure lamp holders (or sockets) are not damaged or loose. If the lamp holders (or sockets) are damaged, corroded, charred, blackened or loose, contact a qualified electrician for proper replacement.
- Please refer to the ballast compatibility guide located at www.philips.com/instantfit.

Product data

General Information	
Cap-Base	GX24Q-3 [GX24q-3]
Nominal lifetime	40,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	835 [CCT of 3500K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	1,200 lm
Correlated Color Temperature (Nom)	3500 K
Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	10.5 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V

Temperature	
Ambient temperature range	-4 °F to 95 °F
T-Case Maximum (Nom)	171 °F

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Product Length	100 mm

Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	No
Approval Marks	CE marking UL certificate RoHS compliance KEMA Keur certificate

LED InstantFit Lamps


Energy Consumption kWh/1000 h	14.5 kWh

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677458423
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677458428

Product Data


Order product name	10.5PL-C/T LED/26V-3500 IF 4P 10/1
Full product name	10.5PL-C/T LED/26V-3500 IF 4P 10/1
Order code	458422
Material Nr. (12NC)	929001181304

Dimensional drawing




Product	D1	D2	A1	A2	A3
10.5PL-C/T LED/26V-3500 IF 4P 10/1	1 inch	1-3/16 inch	3-15/16 inch	4-3/8 inch	5 inch

Photometric data



Light Distribution Diagram - 10.5PL-C/T LED/26V-3500 IF 4P 10/1



Spectral Power Distribution Colour - 10.5PL-C/T LED/26V-3500 IF 4P 10/1

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.