



Standard LED bulbs

LEDBulb 6W E27 3000K W A60 1BL/6 BR

Standard LED bulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize maintenance costs. The Standard LED bulb is the perfect bulb for your basic lighting needs. It provides the beautiful light and performance you expect from the LED technology at an affordable price.

Product data


General Information		Wattage Equivalent	
Cap-Base	E27 [E27]	40 W	
Nominal lifetime	25,000 hour(s)	Starting Time (Nom)	
Switching Cycle	50,000	0.5 s	
Lighting Technology	LED	Warm-up time to 60% light	
EU RoHS compliant	Yes	0.5 s	
Light Technical		Power Factor (Fraction)	
Color Code	830 [CCT of 3000K]	0.92	
Beam Angle (Nom)	150 degree(s)	Voltage (Nom)	
Luminous Flux	600 lm	100-240 V	
Color Designation	White (WH)	Temperature	
Correlated Color Temperature (Nom)	3000 K	T-Case Maximum (Nom)	
Luminous Efficacy (rated) (Nom)	100.00 lm/W	80 °C	
Color Consistency	ANSI	Controls and Dimming	
Color rendering index (CRI)	80	Dimmable	
LLMF At End Of Nominal Lifetime (Nom)	70 %	No	
Operating and Electrical		Mechanical and Housing	
Line Frequency	50 to 60 Hz	Bulb Finish	
Input Frequency	50 to 60 Hz	Frosted	
Power Consumption	6 W	Bulb Shape	
		A60 [A 60mm]	
		Product Data	
		Order product name	
		LEDBulb 6W E27 3000K W A60 1BL/6 BR	
		Full product name	
		LEDBulb 6W E27 3000K W A60 1BL/6 BR	
		Full product code	
		871869667869500	
		Order code	
		929001195191	
		Material Nr. (12NC)	
		929001195191	

Standard LED bulbs

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696678695
Numerator - Packs per outer box	6


EAN/UPC - Case	8718696678701
----------------	---------------

Dimensional drawing



Product	D	C
LEDBulb 6W E27 3000K W A60 1BL/6 BR	60 mm	110 mm

Photometric data



Light Distribution Diagram - LEDBulb 6W E27 3000K W A60 1BL/6 BR

Spectral Power Distribution Colour - LEDBulb 6W E27 3000K W A60 1BL/6 BR

