



Standard LED bulbs

LEDBulb 9W E27 6500K W A19 1PF/6 MX

Standard LED bulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize maintenance costs. The Standard LED bulb is the perfect bulb for your basic lighting needs. It provides the beautiful light and performance you expect from the LED technology at an affordable price.


Product data

General Information		Wattage Equivalent	
Cap-Base	E27 [E27]	60 W	
Nominal lifetime	25,000 hour(s)	Starting Time (Nom)	
Switching Cycle	50,000	0.5 s	
Lighting Technology	LED	Warm-up time to 60% light	
EU RoHS compliant	Yes	0.5 s	
Light Technical		Power Factor (Fraction)	
Color Code	865 [CCT of 6500K]	0.92	
Beam Angle (Nom)	150 degree(s)	Voltage (Nom)	
Luminous Flux	806 lm	100-240 V	
Color Designation	Cool Daylight	Temperature	
Correlated Color Temperature (Nom)	6500 K	T-Case Maximum (Nom)	
Luminous Efficacy (rated) (Nom)	89.56 lm/W	80 °C	
Color Consistency	ANSI	Controls and Dimming	
Color rendering index (CRI)	80	Dimmable	
LLMF At End Of Nominal Lifetime (Nom)	70 %	No	
Operating and Electrical		Mechanical and Housing	
Line Frequency	50 to 60 Hz	Bulb Finish	
Input Frequency	50 to 60 Hz	Frosted	
Power Consumption	9 W	Bulb Shape	
		A19 [A 19mm]	
		Product Data	
		Order product name	
		LEDBulb 9W E27 6500K W A19 1PF/6 MX	
		Full product name	
		LEDBulb 9W E27 6500K W A19 1PF/6 MX	
		Order code	
		929001195441	
		Material Nr. (12NC)	
		929001195441	
		Numerator - Quantity Per Pack	
		1	

Standard LED bulbs


EAN/UPC - Product/Case	046677462918
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677462913

Dimensional drawing



Product	D	C
LEDBulb 9W E27 6500K W A19 1PF/6 MX	60 mm	110 mm

Photometric data



Light Distribution Diagram - LEDBulb 9W E27 6500K W A19 1PF/6 MX

Spectral Power Distribution Colour - LEDBulb 9W E27 6500K W A19 1PF/6 MX

