



CorePro LED PLC 2P



CorePro LED PLC 6.5W 830 2P G24d-2

The CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings and is environmentally friendly.

Product data

General Information	
Cap base	G24d-2
Nominal lifetime	30,000 h
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes

Light Technical	
Colour Code	830 [CCT of 3000K]
Beam angle (nom.)	120 degree(s)
Luminous Flux	650 lm
Colour designation	White (WH)
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (nom.)	92.31 lm/W
Colour consistency	<6
Colour rendering index (CRI)	83
LLMF at end of nominal lifetime (nom.)	70 %
Photobiological safety according to EN 62471	RG0

Operating and Electrical	
Line Frequency	50 to 60 Hz


Input frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp current (max.)	35 mA
Lamp current (min.)	25 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
LED alternative to fluorescent lamp power	18 W
Inrush current at mains	3.4
Max. lamp no. on MCB B type 10A — Mains	123
Max. lamp no. on MCB B type 10A — EM ballast without Comp. Cap.	150
Max. lamp no. on MCB B type 10A — EM ballast with Comp. Cap.	30
Max. lamp no. on MCB B type 16A — Mains	197
Max. lamp no. on MCB B type 16A — EM ballast without Comp. Cap.	220
Max. lamp no. on MCB B type 16A — EM ballast with Comp. Cap.	49
Ballast Compatibility	EM

CorePro LED PLC 2P

Temperature	
Ambient temperature range	-20°C to 35°C
T-Case maximum (nom.)	65 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb material	Plastic
Product length	100 mm
Bulb shape	PL-C
Approval and Application	
Energy Efficiency Class	F
Energy-saving product	Yes
Approval marks	TUV CE marking RoHS compliance KEMA Keur certificate



Energy consumption kWh/1,000 hours	7 kWh
EPREL registration number	403556
Product Data	
Order product name	CorePro LED PLC 6.5W 830 2P G24d-2
Full product name	CorePro LED PLC 6.5W 830 2P G24d-2
Full EOC	871869654127200
Order code	54127200
Material no. (12 NC)	929001201402
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696541272
Numerator – packs per outer box	10
EAN/UPC - Case	8718696541289

Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 830 2P G24d-2	24.3 mm	28.4 mm	105.8 mm	125 mm	147.6 mm

Photometric data




General uniform lighting - CorePro LED PLC 6.5W 830 2P G24d-2

Light Distribution Diagram - CorePro LED PLC 6.5W 830 2P G24d-2


CorePro LED PLC 2P

Photometric data




Spectral Power Distribution Colour - CorePro LED PLC 6.5W 830 2P G24d-2


Lifetime




Life Expectancy Diagram - CorePro LED PLC 6.5W 830 2P G24d-2



Life Expectancy Diagram - CorePro LED PLC 6.5W 830 2P G24d-2




Life Expectancy Diagram - CorePro LED PLC 6.5W 830 2P G24d-2



Lumen Maintenance Diagram - CorePro LED PLC 6.5W 830 2P G24d-2

CorePro LED PLC 2P

Lifetime



Lumen Maintenance Diagram - CorePro LED PLC 6.5W 830 2P G24d-2

