

MASTER VALUE LEDspot MV

MASTER LEDspotMV VLE D 3.5-35W GU10 827 60D

Delivering a warm, halogen-like accent beam, the MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it achieves more natural colours, creating cosy and comfortable ambience for residential and hospitality projects, and emphasising the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. The MASTER VALUE also offers more energy savings than normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap base	GU10 [GU10]
Nominal lifetime	35,000 h
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Colour Code	827 [CCT of 2700K]
Beam angle (nom.)	60 degree(s)

Luminous Flux	305 lm
Luminous intensity (nom.)	350 cd
Colour designation	Warm White (WW)
Correlated Colour Temperature	2700 K
Luminous efficacy (rated) (nom.)	87.14 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux in 90° cone (rated)	265 lm

MASTER VALUE LEDspot MV

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	3.5 W
Lamp current (nom.)	19 mA
Wattage equivalent	35 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (nom.)	220-240 V

Temperature	
T-Case maximum (nom.)	80 °C


Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb shape	PAR16 [PAR 2 inch/50 mm]

Approval and Application	
Energy-saving product	Yes
Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	4 kWh


Product Data	
Order product name	MAS LEDspotMV VLE D 3.5-35W GU10 827 60D
Full product name	MASTER LEDspotMV VLE D 3.5-35W GU10 827 60D
Full EOC	871869656300700
Order code	56300700
Material no. (12 NC)	929001215802
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718696563007
Numerator – packs per outer box	10
EAN/UPC - Case	8718696563014

Dimensional drawing




Product	D	C
MAS LEDspotMV VLE D 3.5-35W GU10 827 60D	50 mm	56 mm

Photometric data




Spectral Power Distribution Colour - MAS LEDspotMV VLE D 3.5-35W GU10 827 60D



Light Distribution Diagram - MAS LEDspotMV VLE D 3.5-35W GU10 827 60D

MASTER VALUE LEDspot MV

Photometric data



General uniform lighting - MAS LEDspotMV VLE D 3.5-35W GU10 827 60D

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.