



MASTER Plastic LEDbulbs

MAS LEDbulb DT 6-40W A60 E27 827 FR

The MASTER Plastic LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to incandescent lamps. They are particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 holder and designed for retrofit replacement of incandescent bulbs, MASTER Plastic LEDbulb delivers huge energy savings of up to 80% compared with traditional incandescent lamps and provides excellent quality of light. By offering a lifetime of 25,000 hours it lowers maintenance costs. They can be used together with most leading-edge dimmers, enabling further efficiencies while helping to create the desired atmosphere.

Warnings and Safety

- \cdot Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- · Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	822-827 [tunable warm white]
Beam Angle (Nom)	200 degree(s)
Luminous Flux	470 lm
Color Designation	Warm White (WW)
Luminous Efficacy (rated) (Nom)	78.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

Datasheet, 2023, December 6 data subject to change

MASTER Plastic LEDbulbs


LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6 W
Lamp Current (Nom)	35 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted

Bulb Shape	A60 [A 60mm]	
Approval and Application		
Energy Saving Product	Yes	
Suitable For Accent Lighting	No	
Energy Consumption kWh/1000 h	6 kWh	
Product Data		
Order product name	MAS LEDbulb DT 6-40W A60 E27 827 FR	
Full product name	MAS LEDbulb DT 6-40W A60 E27 827 FR	
Full product code	871869657791200	
Order code	929001233202	
Material Nr. (12NC)	929001233202	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718696577912	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8718696577929	


Dimensional drawing

Product	D	С
MAS LEDbulb DT 6-40W A60 E27 827 FR	60 mm	110 mm

Photometric data




General uniform lighting - MAS LEDbulb DT 6-40W A60 E27 827 FR



Light Distribution Diagram - MAS LEDbulb DT 6-40W A60 E27 827 FR

MASTER Plastic LEDbulbs

Photometric data



Spectral Power Distribution Colour - MAS LEDbulb DT 6-40W A60 E27 827 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.