PHILIPS

Lighting



T8

14T8/48-4000 IF 10/1 EasySmart

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	2,100 lm
Correlated Color Temperature (Nom)	4000 K
Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	14 W
Lamp Current (Max)	240 mA
Lamp Current (Min)	130 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277, 347 V

Temperature	
Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	40 °C

Controls and Dimming	
Dimmable	Wireless Dim

Mechanical and Housing	
Product Length	1,200 mm

Approval and Application	
Energy Saving Product	Yes
Approval Marks	UL certificate RoHS compliance DLC compliance

T8


Energy Certifications	DLC Standard

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677466473
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677466478

Product Data


Order product name	14T8/48-4000 IF 10/1 EasySmart
Full product name	14T8/48-4000 IF 10/1 EasySmart
Order code	929001281304
Material Nr. (12NC)	929001281304

Dimensional drawing




Product	D1	D2	A1	A2	A3
14T8/48-4000 IF 10/1 EasySmart	25.7 mm	26.3 mm	1,198 mm	1,205 mm	1,212 mm


Photometric data



Spectral Power Distribution Colour - 14T8/48-4000 IF 10/1 EasySmart




Light Distribution Diagram - 14T8/48-4000 IF 10/1 EasySmart




General uniform lighting - 14T8/48-4000 IF 10/1 EasySmart

T8

Lifetime



Life Expectancy Diagram - 14T8/48-4000 IF 10/1 EasySmart



Lumen Maintenance Diagram - 14T8/48-4000 IF 10/1 EasySmart

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.