



LED PAR38

13.5PAR38/YELLOW/FLOOD/ND ULW 1/4

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

Product data

General Information		
Cap-Base	E26 [Single Contact Medium Screw]	
Nominal lifetime	10,950 hour(s)	
Switching Cycle	10,000	
Rated Lifetime (Hours)	10,950 hour(s)	
Lighting Technology	LED	
EU RoHS compliant	Yes	
Light Technical		
Color Designation	Yellow	
Color Consistency	<6	
LLMF At End Of Nominal Lifetime (Nom)	70 %	
Operating and Electrical		
Line Frequency	60 Hz	
Input Frequency	60 Hz	
Power Consumption	13.5 W	
Lamp Current (Nom)	165 mA	
Starting Time (Nom)	0.5 s	
Warm-up time to 60% light	0.5 s	
Power Factor (Fraction)	0.5	
Voltage (Nom)	120 V	
Temperature		
T-Case Maximum (Nom)	65 °C	

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	PAR38 [PAR 4.75 inch/121mm]
Approval and Application	
Suitable For Accent Lighting	Yes
EyeComfort	Yes
Product Data	
Order product name	13.5PAR38/YELLOW/FLOOD/ND ULW 1/4
Full product name	13.5PAR38/YELLOW/FLOOD/ND ULW 1/4
Order code	929001395605
Material Nr. (12NC)	929001395605
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677473723
Numerator - Packs per outer box	4
EAN/UPC - Case	50046677473728

LED PAR38

Dimensional drawing



13.5PAR38/YELLOW/FLOOD/ND ULW 1/4 122 mm 132 mm	Product	D	с
	13.5PAR38/YELLOW/FLOOD/ND ULW 1/4	122 mm	132 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, November 23 - data subject to change