


Essential LED bulbs

Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX

Essential LEDbulbs are compatible with existing fixtures with a E27 holder and are designed for retrofit replacement of incandescent, halogen and energy saving bulbs. They deliver huge energy savings and minimize initial investment

Product data

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	10,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	130 degree(s)
Luminous Flux	280 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	80.00 lm/W
Color Consistency	<7
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3.5 W
Lamp Current (Nom)	56 mA
Wattage Equivalent	25 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.5
Voltage (Nom)	110-130 V

Temperature	
T-Case Maximum (Nom)	50 °C

Controls and Dimming	
Dimmable	No


Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A19 [A 19mm]

Product Data	
Order product name	Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX
Full product name	Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX
Full product code	871869676011600
Order code	929001806541
Material Nr. (12NC)	929001806541
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696760116
Numerator - Packs per outer box	6

Essential LED bulbs


EAN/UPC - Case	8718696760123

Dimensional drawing




Product	D	C
Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX	58 mm	104 mm


Photometric data



Spectral Power Distribution Colour - Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX




General uniform lighting - Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX




Light Distribution Diagram - Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX

Essential LED bulbs

Lifetime





Lumen Maintenance Diagram - Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX

Life Expectancy Diagram - Ess LEDBulb 3.5-25W E27 3000K A19 2PK MX

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.