



MASTER LEDtube T8 Ultra Efficient



MAS LEDtube 1500mm UE 20W 840 T8

With energy prices rising and the EU's Green Deal² continuing to fund energy efficient building renovations, many are looking into make their company's lighting more sustainable. The new Philips MASTER LEDtube Ultra Efficient T8 is a true breakthrough on the way to more sustainable lighting. It replaces your current fluorescent tube or LED tube directly and offers immediately great energy cost reduction as well as a much longer lifetime!

Product data

General Information	
Cap base	G13 ROT (Rotating) [Medium Bi-Pin Fluorescent]
Nominal lifetime	75,000 h
Switching Cycle	200,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes
Light Technical	
Colour Code	840 [CCT of 4000K]
Beam angle (nom.)	160 degree(s)
Luminous Flux	3,700 lm
Colour designation	Cool White (CW)
Correlated Colour Temperature	4000 K
Luminous efficacy (rated) (nom.)	185 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80

LLMF at end of nominal lifetime (nom.)	70 %
Flickering value (PstLM)	0.5
Stroboscopic effect	0.2
Photobiological safety according to EN 62471	RG0
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	20 W
Lamp current (max.)	103 mA
Lamp current (min.)	85 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
LED alternative to fluorescent lamp power	58 W
Max. lamp no. on MCB B type 10A — Mains	75
Max. lamp no. on MCB B type 10A — EM ballast without Comp. Cap.	75

MASTER LEDtube T8 Ultra Efficient

Max. lamp no. on MCB B type 10A — EM ballast with Comp. Cap.	10
Max. lamp no. on MCB B type 16A — Mains	120
Max. lamp no. on MCB B type 16A — EM ballast without Comp. Cap.	120
Max. lamp no. on MCB B type 16A — EM ballast with Comp. Cap.	16

Temperature

Ambient temperature range	-20°C to 45°C
T-Case maximum (nom.)	60 °C

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Lamp Finish	Frosted
Bulb material	Plastic
Product length	1,500 mm

Approval and Application


Energy Efficiency Class	B
-------------------------	---

Energy-saving product	Yes
Approval marks	RoHS compliance TUV CE marking KEMA Keur certificate
Energy consumption kWh/1,000 hours	20 kWh
EPREL registration number	1205538

Product Data



Order product name	MAS LEDtube 1500mm UE 20W 840 T8
Full product name	MAS LEDtube 1500mm UE 20W 840 T8
Full EOC	871951433976700
Order code	33976700
Material no. (12 NC)	929003067202
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8719514339767
Numerator – packs per outer box	10
EAN/UPC - Case	8719514339774

Dimensional drawing



Product	D1	D2	A1	A2	A3
MAS LEDtube 1500mm UE 20W 840 T8	25.8 mm	28 mm	1,498.8 mm	1,505.9 mm	1,513 mm

Photometric data




General uniform lighting - MAS LEDtube 1500mm UE 20W 840 T8

Spectral Power Distribution Colour - MAS LEDtube 1500mm UE 20W 840 T8


MASTER LEDtube T8 Ultra Efficient

Photometric data




Light Distribution Diagram - MAS LEDtube 1500mm UE 20W 840 T8


Lifetime




Life Expectancy Diagram - MAS LEDtube 1500mm UE 20W 840 T8



Lumen Maintenance Diagram - MAS LEDtube 1500mm UE 20W 840 T8





Life Expectancy Diagram - MAS LEDtube 1500mm UE 20W 840 T8



Lumen Maintenance Diagram - MAS LEDtube 1500mm UE 20W 840 T8

MASTER LEDtube T8 Ultra Efficient

Lifetime



Life Expectancy Diagram - MAS LEDtube 1500mm UE 20W 840 T8

Life Expectancy Diagram - MAS LEDtube 1500mm UE 20W 840 T8

