



GENIE

UAE GENIE 14W CDL B22 1CT/12

Functional non-covered Energy saving lamp, with money saving high quality light and compact design. This lamp is small enough to fit neatly wherever you need extra bright light at home, enables easy replacement of most incandescent lamp all the way.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.


Product data

| General Information | | LLMF At End Of Nominal Lifetime (Nom) | |
|------------------------------------|--------------------------------|---------------------------------------|-------------|
| Cap-Base | B22 [B22] | | 65 % |
| Nominal lifetime | 10,000 hour(s) | Operating and Electrical | |
| Switching Cycle | 10,000 | Line Frequency | 50 or 60 Hz |
| Rated Lifetime (Hours) | 10,000 hour(s) | Input Frequency | 50 or 60 Hz |
| Lighting Technology | Compact Fluorescent Integrated | Power Consumption | 14.0 W |
| Light Technical | | Lamp Current (Nom) | 100 mA |
| Color Code | 865 [CCT of 6500K] | Starting Time (Nom) | 0.3 s |
| Luminous Flux | 760 lm | Power Factor (Fraction) | 0.6 |
| Color Designation | Cool Daylight | Voltage (Nom) | 220-240 V |
| Chromaticity Coordinate X (Nom) | 313 | Controls and Dimming | |
| Chromaticity Coordinate Y (Nom) | 337 | Dimmable | No |
| Correlated Color Temperature (Nom) | 6500 K | | |
| Luminous Efficacy (rated) (Nom) | 54 lm/W | | |
| Color rendering index (CRI) | 82 | | |

| | |
|---------------------------------|------------------------------|
| Mechanical and Housing | |
| Bulb Shape | Stick |
| Approval and Application | |
| Mercury (Hg) Content (Max) | 2.0 mg |
| Energy Consumption kWh/1000 h | 14 kWh |
| Product Data | |
| Order product name | UAE GENIE 14W CDL B22 1CT/12 |
| Full product name | UAE GENIE 14W CDL B22 1CT/12 |

| | |
|---------------------------------|-----------------|
| Full product code | 871869640942800 |
| Order code | 929689100601 |
| Material Nr. (12NC) | 929689100601 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696409428 |
| Numerator - Packs per outer box | 12 |
| EAN/UPC - Case | 8718696409435 |

Dimensional drawing



| Product | D (max) | C (max) | F (max) |
|------------------------------|---------|----------|---------|
| UAE GENIE 14W CDL B22 1CT/12 | 35.0 mm | 130.5 mm | 44.4 mm |

