



# Softone ESaver Candle

## Softone Candle 12W WW E14 220-240V 1PF/6

Standard energy-saving lamps in the shape of an incandescent candle lamp

### Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

### Product data


General Information		LLMF At End Of Nominal Lifetime (Nom) 65 %	
Cap-Base	E14 [E14]		
Nominal lifetime	10,000 hour(s)		
Switching Cycle	30,000		
Rated Lifetime (Hours)	10,000 hour(s)		
Lighting Technology	Compact Fluorescent Integrated		
Light Technical		Operating and Electrical	
Color Code	827 [CCT of 2700K]	Line Frequency	50 or 60 Hz
Luminous Flux	610 lm	Input Frequency	50 or 60 Hz
Color Designation	Warm White (WW)	Power Consumption	12.0 W
Chromaticity Coordinate X (Nom)	463	Lamp Current (Nom)	80 mA
Chromaticity Coordinate Y (Nom)	420	Starting Time (Nom)	1.0 s
Correlated Color Temperature (Nom)	2700 K	Power Factor (Fraction)	0.6
Luminous Efficacy (rated) (Nom)	51 lm/W	Voltage (Nom)	220-240 V
Color rendering index (CRI)	82		
		Controls and Dimming	
		Dimmable	No
		Mechanical and Housing	
		Bulb Shape	B45 [B 45mm]

# Softone ESaver Candle

Approval and Application	
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	12 kWh
Product Data	
Order product name	Softone Candle 12W WW E14 220-240V 1PF/6
Full product name	Softone Candle 12W WW E14 220-240V 1PF/6
Full product code	871829168095600

Order code	68095600
Material Nr. (12NC)	929689139501
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291680956
Numerator - Packs per outer box	6
EAN/UPC - Case	8718291680963

## Dimensional drawing



Product	D (max)	C (max)	F (max)
Softone Candle 12W WW E14 220-240V 1PF/6	46.5 mm	126.0 mm	43 mm

