



Softone Flame

Softone Flame Candle 5W E14 B39 1PF/6

High quality flame colored energy saving lamps which is decoratively shaped to complement your luminaire.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	10,000 hour(s)
Switching Cycle	30,000
Rated Lifetime (Hours)	10,000 hour(s)
Lighting Technology	Compact Fluorescent Integrated
Light Technical	
Luminous Flux	172 lm
Color Designation	Flame
Chromaticity Coordinate X (Nom)	463
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2200 K
Luminous Efficacy (rated) (Nom)	38 lm/W
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	65 %

Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	5.0 W
Lamp Current (Nom)	40 mA
Starting Time (Nom)	1.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	B39 [B 39mm]

Approval and Application	
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg

Softone Flame

Energy Consumption kWh/1000 h	5 kWh
Product Data	
Order product name	Softone Flame Candle 5W E14 B39 1PF/6
Full product name	Softone Flame Candle 5W E14 B39 1PF/6
Full product code	872790090520501
Order code	929689199102

Material Nr. (12NC)	929689199102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900905205
Numerator - Packs per outer box	6
EAN/UPC - Case	8718291129011

Dimensional drawing

Product	D (max)	C (max)	F (max)
Softone Flame Candle 5W E14 B39 1PF/6	40.5 mm	107.5 mm	39 mm

