



# **GENIE**

# GENIE 8W CDL B22 220-240V 1CT/12

Functional non-covered Energy saving lamp, with money saving high quality light and compact design. This lamp is small enough to fit neatly wherever you need extra bright light at home, enables easy replacement of most incandescent lamp all the way.

#### **Warnings and Safety**

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### **Product data**

General Information			
Cap-Base	B22 [B22]		
Nominal lifetime	8,000 hour(s)		
Switching Cycle	5,000		
Rated Lifetime (Hours)	8,000 hour(s)		
Lighting Technology	Compact Fluorescent Integrated		
Light Technical			
Color Code	865 [CCT of 6500K]		
Luminous Flux	400 lm		
Color Designation	Cool Daylight		
Chromaticity Coordinate X (Nom)	313		
Chromaticity Coordinate Y (Nom)	337		
Correlated Color Temperature (Nom)	6500 K		
Luminous Efficacy (rated) (Nom)	50 lm/W		
Color rendering index (CRI)	80		

50 or 60 Hz
50 or 60 Hz
8 W
60 mA
0.3 s
0.6
220-240 V
No

Datasheet, 2023, September 4 data subject to change

## **GENIE**

Mechanical and Housing	
Bulb Shape	Stick
Approval and Application	
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	8 kWh
Product Data	
Order product name	GENIE 8W CDL B22 220-240V 1CT/12
Full product name	GENIE 8W CDL B22 220-240V 1CT/12

Full product code	871829173251800		
Order code	929689423499		
Material Nr. (12NC)	929689423499		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8718291732518		
Numerator - Packs per outer box	12		
EAN/UPC - Case	8718291732525		

## Dimensional drawing

Product	D (max)	C (max)	F (max)
GENIE 8W CDL B22 220-240V 1CT/12	35.0 mm	105.5 mm	44.4 mm

