



# **GENIE**

## GENIE 11W CDL E14 220-240V 1CT/12

Functional non-covered Energy saving lamp, with money saving high quality light and compact design. This lamp is small enough to fit neatly wherever you need extra bright light at home, enables easy replacement of most incandescent lamp all the way.

#### **Warnings and Safety**

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### **Product data**

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	10,000 hour(s)
Switching Cycle	5,000
Rated Lifetime (Hours)	10,000 hour(s)
Lighting Technology	Compact Fluorescent Integrated
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	590 lm
Color Designation	Cool Daylight

Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	52 lm/W
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	65 %

Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	11 W


Datasheet, 2023, April 30 data subject to change

### **GENIE**

Lamp Current (Nom)	80 mA
Starting Time (Nom)	0.3 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Stick
Approval and Application	
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	11 kWh

Product Data			
Order product name	GENIE 11W CDL E14 220-240V 1CT/12		
Full product name	GENIE 11W CDL E14 220-240V 1CT/12		
Full product code	871829173249500		
Order code	929689433699		
Material Nr. (12NC)	929689433699		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8718291732495		
Numerator - Packs per outer box	12		
EAN/UPC - Case	8718291732501		

### Dimensional drawing



Product	D (max)	C (max)	F (max)
GENIE 11W CDL E14 220-240V 1CT/12	35.0 mm	122.0 mm	44.4 mm

