



Tornado T2

TornadoT2 8y 23W CDL B22 220-240V 1CT/12

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

B22 [B22]
8,000 hour(s)
5,000
8,000 hour(s)
Compact Fluorescent Integrated
865 [CCT of 6500K]
1,450 lm
Cool Daylight
313
337
6500 K
63 lm/W
80

LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	23 W
Lamp Current (Nom)	170 mA
Starting Time (Nom)	0.3 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Spiral


Datasheet, 2023, September 4 data subject to change

Tornado T2

Approval and Application	
Mercury (Hg) Content (Nom)	2 mg
Energy Consumption kWh/1000 h	23 kWh
Product Data	
Order product name	TornadoT2 8y 23W CDL B22 220-240V 1CT/12
Full product name	TornadoT2 8y 23W CDL B22 220-240V 1CT/12
Full product code	871869645054300

Order code	929689858606
Material Nr. (12NC)	929689858606
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696450543
Numerator - Packs per outer box	12
EAN/UPC - Case	8718696450550

Dimensional drawing



Product	D (max)	C (max)	F (max)
TornadoT2 8y 23W CDL B22 220-240V 1CT/12	61.5 mm	117 mm	50.5 mm

