



Energy Saver Decoratives

EL/Can T2 5W

Philips Energy Saver Decorative CFLs provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

General Information		
Cap-Base	E26 [Single Contact Medium Screw]	
Switching Cycle	5,000	
Rated Lifetime (Hours)	8,000 hour(s)	
Lighting Technology	Compact Fluorescent Integrated	
Light Technical		
Color Code	827 [CCT of 2700K]	
Color Designation	Warm White (WW)	
Chromaticity Coordinate X (Nom)	459	
Chromaticity Coordinate Y (Nom)	412	
Correlated Color Temperature (Nom)	2700 K	
Luminous Efficacy (rated) (Nom)	43 lm/W	
Operating and Electrical		
Line Frequency	50 or 60 Hz	

Input Frequency	50 or 60 Hz
Power Consumption	5 W
Lamp Current (Nom)	90 mA
Power Factor (Fraction)	0.55
Voltage (Nom)	110-127 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	EL/Can T2
Product Data	
Order product name	EL/Can T2 5W
Order code	929689962701
Numerator - Quantity Per Pack	1


Datasheet, 2023, September 4 data subject to change

Energy Saver Decoratives


Numerator - Packs per outer box	6
Material Nr. (12NC)	929689962701
Full product name	EL/Can T2 5W
EAN/UPC - Case	50046677422290

EAN/UPC - Product/Case 0466/7422295	EAN/UPC - Product/Case	046677422295
-------------------------------------	------------------------	--------------

Dimensional drawing







Product	D (max)	C (max)	F (max)
EL/Can T2 5W	40.5 mm	103.8 mm	40 mm

