



MASTER PL-Electronic

MASTER PLE-C 11W/827 E27 230-240V 1CT/6

Non-covered energy-saving MASTER lamps – the perfect choice for end users who demand the best performance and reliability. With a wide product range with different wattages, it offers comprehensive choices to suit different usages and applications.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

| General Information | |
|------------------------|--------------------------------|
| Cap base | E27 [E27] |
| Nominal lifetime | 15,000 h |
| Switching Cycle | 20,000 |
| Rated Lifetime (Hours) | 15,000 h |
| Lighting Technology | Compact Fluorescent Integrated |

| Light Technical | |
|---------------------------------|--------------------|
| Colour Code | 827 [CCT of 2700K] |
| Luminous flux (min.) | 540 lm |
| Luminous Flux | 600 lm |
| Colour designation | Warm White (WW) |
| Chromaticity Coordinate X (Nom) | 466 |
| Chromaticity Coordinate Y (Nom) | 422 |

| | |
|--|---------|
| Correlated Colour Temperature | 2700 K |
| Luminous efficacy (rated) (nom.) | 55 lm/W |
| Colour rendering index (CRI) | 82 |
| LLMF at end of nominal lifetime (nom.) | 65 % |

| Operating and Electrical | |
|--------------------------|-------------|
| Line Frequency | 50 or 60 Hz |
| Input frequency | 50 or 60 Hz |
| Power Consumption | 11 W |
| Lamp current (nom.) | 75 mA |
| Power Factor (Fraction) | 0.62 |
| Voltage (nom.) | 230-240 V |

MASTER PL-Electronic

Controls and Dimming

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Mechanical and Housing

| | |
|------------|-------|
| Bulb shape | Stick |
|------------|-------|

Approval and Application

| | |
|-----------------------------|---------|
| Mercury (Hg) content (nom.) | 1.41 mg |
|-----------------------------|---------|


| | |
|------------------------------------|--------|
| Energy consumption kWh/1,000 hours | 11 kWh |
|------------------------------------|--------|

Product Data

| | |
|--------------------|---|
| Order product name | MASTER PLE-C 11W/827 E27 230-240V 1CT/6 |
|--------------------|---|

| | |
|-----------------------------------|---|
| Full product name | MASTER PLE-C 11W/827 E27 230-240V 1CT/6 |
| Full EOC | 871150026368100 |
| Order code | 26368100 |
| Material no. (12 NC) | 929730982709 |
| Local order code | 11ESPLE |
| SAP numerator – quantity per pack | 1 |
| EAN/UPC – Product/Case | 8711500263681 |
| Numerator – packs per outer box | 6 |
| EAN/UPC – Case | 8718291685470 |

Dimensional drawing



| Product | D (max) | C (max) | F (max) |
|---|---------|----------|---------|
| MASTER PLE-C 11W/827 E27 230-240V 1CT/6 | 28.0 mm | 141.2 mm | 40.3 mm |

