



Designer Floodlight LED

DFL7 RSP 16LEDs 700mA NW Gen2 Rectangular Spot

DFL7 RSP 16LEDs 700mA NW Gen2 Rectangular Spot - 102 lm/W

The Gardco Designer Flood LED combines impressive floodlighting performance and control with the efficiency and energy savings of LEDs. Based on the popular Designer Floodlight Series, this updated line of architectural luminaires is specifically designed for advanced LED arrays. The housing of the Designer Flood LED provides advanced thermal management to dissipate heat, thereby maximizing the inherent sustainability and performance of the LEDs. While the housing shape is redesigned to better suit the source, the best elements of the Designer Floodlight Series are retained, including the die cast aluminum construction, rugged mounting knuckle, integral splice box, and tamper-resistant fasteners, all protected by a textured polyester powdercoat finish, silicone seals and moisture-proof gasketing. Whether ground, wall, ceiling or pole mounted, its timeless form is always appropriate, comfortably blending into its surroundings. It is performance, however, that distinguishes Gardco and the Designer Flood LED. When used in place of HID systems, the Designer Flood LED offers significant energy savings. Numerous precision optical systems are available, delivering the right pattern for any application. Free from streaks and striations, these distributions place the intended target in its best light. Having the right distribution pattern is only half of the battle. Frequently, setback considerations and architectural limitations make placing the luminaire extremely challenging. With its numerous mounting options, the Designer Flood LED addresses these concerns practically and handsomely. Mounting accessories are specifically designed to complement the luminaire, and with its integral splice box, the luminaire can be mounted flush at grade. Combined with 358° horizontal and 180° vertical rotational ability, you have a precision lighting instrument that can only come from Gardco.

Designer Floodlight LED

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	70
Photometric Distribution Type	Horizontal Spot
Mounting	Ground / Floor Wall

Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	38

Mechanical and Housing	
Shape	Rectangular
Material	Aluminum

Approval and Application	
Safety Listing	UL
Energy Certifications	DLC Standard

DesignLights Consortium Qualified Product List	
Product List	
IP Rating	IP66

Initial Performance (IEC Compliant)	
Luminaire Lumens	3893
Efficacy	102 lm/W

Product Data	
Order product name	DFL7 RSP 16LEDs 700mA NW Gen2 Rectangular Spot
Order code	DFL7-RSP-16L-700-NW-G2
Material Nr. (12NC)	GAR7000777
Catalog Number	DFL7-RSP-16L-700-NW-G2
Catalog Number Description	DFL7 RSP 16LEDs 700mA NW Gen2 Rectangular Spot

