



111 LED Mini Sconce

111L Mini Sconce Gen2, 16LEDs, 550mA, 3000K, Type 2

111L Mini Sconce Gen2, 16LEDs, 550mA, - 3000K, Type 2 - 101 lm/W

Gardco 111L LED mini sconce luminaires are compact in size, perfect for low mounting height wall mount applications. 111 LED luminaires are designed to integrate naturally to wall surfaces. 111 LED luminaires are available with three (3) different distribution patterns, providing full cutoff performance (in the normal downlight position) and featuring LED arrays. Luminaires provide performance excellence and advanced Gardco LED thermal management technology. High performance Class 1 LED systems offer potential energy savings of 50 % or more compared to HID systems. 111 LED luminaires are also available with 0-10V Dimming.

Product data

General Information

Lamp Source Code	LED
Colour Temperature	3000K
CRI	70
Photometric Distribution Type	Type II
Mounting	Wall
B.U.G. Rating	BIUOGO

Operating and Electrical

Voltages	UNIV V
Luminaire Input Watts	29

Mechanical and Housing

Shape	Rectangular
-------	-------------

Approval and Application

Safety Listing	UL
DesignLights Consortium Qualified	DesignLights Consortium Qualified Product
Product List	List

Initial Performance (IEC Compliant)

Luminaire Lumens	2500
Efficacy	101 lm/W

Application Conditions

Max Ambient Temp	+40 °C
------------------	--------

111 LED Mini Sconce

Min Ambient Temp	-40 °C
Product Data	
Order product name	111L Mini Sconce Gen2, 16LEDs, 550mA, 3000K, Type 2
Order code	111L-16L-550-WW-G2-2

Material Nr. (12NC)	GAR7003675
Catalog Number	111L-16L-550-WW-G2-2
Catalog Number Description	111L Mini Sconce Gen2, 16LEDs, 550mA, 3000K, Type 2

