



EcoForm LED site and area G2 - small (ECF-S)

EcoForm, Small, 48 LEDs, 900mA, 4000K, Generation 2, Auto Front Row

EcoForm, Small, 48 LEDs, 900mA, 4000K, Generation 2, Auto Front Row - 138 lm/W

In any outdoor site and area project, the next generation of Gardco EcoForm LED site and area luminaires are more than sources of illumination. they offer the best of all worlds: saving energy, saving time, and saving money for significant and enduring value. It's not just about meeting technical requirements. It's about looking out for the best interests of your customers, and going the extra mile to uncover new savings and conveniences!

Product data

General information	
Service tag	Yes
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	70
Photometric Distribution Type	Auto Front Row
Mounting	Pole Arm Wall
B.U.G. Rating	B3U0G2
Awards	DLC QPL
Number Of Pieces	1

Buy American Compliant	Yes
Products	
Operating and electrical	
Voltages	120/208/240/277/347/480 V
Luminaire Input Watts	135
Conduit Connection	7/8 inch knockout
Mechanical and housing	
Enclosure	Metal and Plastic

EcoForm LED site and area G2 - small (ECF-S)

Approval and application

Safety Listing	UL
Energy Certifications	IDA Dark Sky Approved cULus DLC Standard DLC Premium
IP Rating	IP65 [Dust penetration-protected, jet-proof]
Vibration Rating	3.0G

Initial performance (IEC compliant)

Luminaire Lumens	18700
Efficacy	138 lm/W

Application conditions

Ambient temperature range	-40 to +40 °C
Max Ambient Temp	+40 °C

Min Ambient Temp	-40 °C
Min Ambient Temp-DUP(do not use)	-40 °C

Product data

Order product name	EcoForm, Small, 48 LEDs, 900mA, 4000K, Generation 2, Auto Front Row
Order code	ECF-S-48L-900-NW-G2-AFR
Material Nr. (12NC)	GAR7003734
Catalog Number	ECF-S-48L-900-NW-G2-AFR
Catalog Number Description	EcoForm, Small, 48 LEDs, 900mA, 4000K, Generation 2, Auto Front Row

