
PHILIPS EcoStyle


Installation instructions

Instructions de montage	Instrucciones de montaje	Kokoonpano- ja kiinnitysohjeet	Szerelési utasítás
Montageanletiung	Instruções de montagem	Montaj yönergesi	Návod k montázi
Montage instruktic	Monteringsinstruktioner	Odhgiez synarmologhshz	Инструкция по монтажу
Instruzioni di montaggio	Monteringsvejledning	Instrukcja montazu	Návod k montázi



	min	max	kg	P max	GLOW WIRE 650°C	IK02
ST440T LED27S/CH PSU WB II BK	10°C	40°C	1	51.5W	●	●
ST440T LED27S/CH PSU WB II WH	10°C	40°C	1	51.5W	●	●
ST440T LED19S/FMT PSU WB II BK	10°C	40°C	1	36 W	●	●
ST440T LED19S/FMT PSU WB II WH	10°C	40°C	1	36 W	●	●
ST440T LED27S/CRW PSU MB II BK	10°C	40°C	1	35.5W	●	●
ST440T LED27S/CRW PSU MB II WH	10°C	40°C	1	35.5W	●	●

ST440T





GA69




GLOBAL Trac Base


Connection
230 V AC, 16 A, 3.7 kW








DRIVER	Xitanium 50W LH 0.7-1.5A	LED Driver 36W 0.3-1A 48V I 230V
Inom(A)	0,32	0,2
Imax(A)	5,3	6
Tref(us)	700 (@ Imax 50%)	55
MCB	**Max. products**	**Max. products**
B-16A	30	39



4443 160 08991
Version date : 24/04/15
Printed in The EU
Data subject to change without notice
© 12 / 2015, Koninklijke Philips Electronics N.V. All rights reserved
Keep for future reference: www.philips.com/lighting

PHILIPS



Luminaire shall be
mounted out of arms reach!

