

GreenSpace Accent Elbow


Installation instructions


Instructions de montage
Montageanleitung
Montage instruktic
Instruzioni di montaggio
Instrucciones de montaje
Instruções de montagem
Monteringsinstruktioner
Monteringsvejledning
Kokoonpano- ja kiinnitysohjeet
Montaj yönergesi
Odhgiez synarmologhshz
Instrukcja montazu
Szerelési utasítás
Návod k montázi
Инструкция по монтажу
Návod k montázi




		220 V 240 V	IP20	0,8m			min	max	kg	P		GLOW WIRE 650°C
RS342B LED17S/830	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 19 W	•	•
RS342B LED17S/840	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 19 W	•	•
RS342B LED27S/830	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 31 W	•	•
RS342B LED27S/840	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 31 W	•	•
RS342B LED35S/830	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 39 W	•	•
RS342B LED35S/840	•	•	•	•	•	•	0°C	35°C	1,25 kg	max 39 W	•	•













Minimal build-in dimensions





Driver dimensions








1.


444316004791/C
Version date: 22/10/2014
Data Subject to change without notice
Printed in EU
www.philips.com/lighting


PHILIPS















Optical unit changing, and cleaning instructions









Only with soft cloths!







PSU

LED driver 36W 0.3-1A 48V I 230V








PSU


Xitanium 36W LH 0.3-1A 48V I 230V


~ 220-240V



MAIN CABLE

~220-240V







PSU

LED17S & LED27S	
LED driver 36W 0.3-1A 48V I 230V 929000892506	
Inom[A]	0,2
Imax[A]	6
Tref[us]	55
MCB	Max products [pcs]*
B-16A	39

LED35S	
Xitanium 36W LH 0.3-1A 48V I 230V 929000838903	
Inom[A]	0,19
Imax[A]	20
Tref[us]	250
MCB	Max products [pcs]*
B-16A	32

* According to IEC60555 test conditions