Lytecaster Recessed Downlight


R620

01-Nov-11

5-1/4" Aperture Basic Grooved Baffle

Incandesent

Ceiling Opening: 5-1/4" (130mm)



Complete fixture consists of Reflector Trim & Frame-in Kit. Select each separately

Reflector Trim	Frame-in Kit		Lamp		
R620BK	**1002**	Frame Non-IC	75W PAR30L	75W BR30	60W A19
Black	**1000IC**	Frame IC	75W PAR30	65W BR30	40W A19
	1004ICN	Lytening Frame Non-IC	50W PAR30	65W BR30	40W A19
R620WH	**1004ICN**	Lytening Frame IC	50W PAR30	65W BR30	
White	**1004ICRS**	Lytening Remodeler Non-IC	50W PAR30	65W BR30	40W A19
	1004ICRS	Lytening Remodeler IC	50W PAR30	65W BR30	
	1004ICXN	Lytening ICX Frame AirSeal®	75W PAR30L	65W BR30	40W A19

Features

Reflector : Hydroformed aluminum, .032" thick ;
non-yellowing reflective white; integral grooves in black or white.

Accessories

1967B	2 in (51mm). Thick Ceiling Adaptor.

Frame-in Kit

See Frame-In Kit specification sheets for more details.

Finish

All painted finishes are baked powder or enamel.

Markings

cULus listed, suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Canlyte www.canlyte.com
3015 Louis-Amos, Lachine, Québec H8T 1C4 • (514) 636-0670 • (514) 636-0460

PHILIPS
LIGHTOLIER®

Éclairage Encastré Lytecaster


R620

01-Nov-11

5-1/4 po Ouverture, déflecteur à rainures intégrales

Compact Fluorescent

Ouverture du plafond : 5-1/4 po (130mm)



Le luminaire complet comprend la garniture et le cadre de montage : choisir chacun séparément.

Garniture	Cadre de montage		Lampe		
R620BK	**1002**	Cadre Non-IC	75W PAR30L	75W BR30	60W A19
Noir	**1000IC**	Cadre IC	75W PAR30	65W BR30	40W A19
	1004ICN	Lytening Cadre Non-IC	50W PAR30	65W BR30	40W A19
R620WH	**1004ICN**	Lytening Cadre IC	50W PAR30	65W BR30	
Blanc	**1004ICRS**	Lytening Anneau Rénovation Non-IC	50W PAR30	65W BR30	40W A19
	1004ICRS	Lytening Anneau Rénovation IC	50W PAR30	65W BR30	
	1004ICXN	Lytening ICX Cadre AirSeal®	75W PAR30L	65W BR30	40W A19

Caractéristiques

Réflecteur : aluminium hydroformé, .032 po d'épaisseur ;
fini blanc ne jaunissant pas ; rainures intégrales en noir ou blanc.

Accessoires

1967B	Kit plafond de 2 po (51mm) max.

Cadre de Montage

Pour les caractéristiques des cadres de montage, voir les fiches techniques appropriées.

Fini

Tous les finis peints sont en poudre ou en émail cuit.

Marquage

Homologué cULus ; convient aux endroits humides.

Information Projet **Type:**

Nom Projet:

No. Cat.:

Lampe(s):

Notes:

Canlyte www.canlyte.com
3015 Louis-Amos, Lachine, Québec H8T 1C4 • (514) 636-0670 • (514) 636-0460

PHILIPS LIGHTOLIER