

PHILIPS



Garage & Canopy

SoftView



Parking **with confidence**

Philips Gardco SoftView LED parking garage luminaires use indirect illumination and uplight to reduce glare and eliminate the cave effect so that your patrons can feel comfortably secure. Utilizing LED technology reduces energy and maintenance costs compared to conventional technologies, and savings are further enhanced through a variety of dimming and control options.



Features and benefits

- Edge lit technology creates soft, uniform illumination that increases visual comfort without compromising performance or exposing viewers to harsh glare
- Uplight directed onto the ceiling eliminates cave effect
- Achieves up to 122 LPW for lower energy costs even during constant operation
- A variety of lumen packages available, with output ranging from approximately 3000 - 8600 lumens
- Type 5 and Concentrated Downlight distributions available to create your ideal parking garage environment
- Cool, neutral, and warm white color temperatures
- Long LED life reduces maintenance time and expenses compared to conventional technologies
- Added flexibility and further enhance savings through optional controls, including 0-10V dimming, motion response and Wireless controls

Ordering guide


Example: SVPG-168L-1200-NW-SM-5-UNV-WH

Luminaire	LED Count	System Drive Current	Color Temperature	Mounting	Distribution	Emergency	Voltage	Control Options	Luminaire Options	Finish
SVPG	168L									
SVPG SoftView Parking Garage	168L 168 LEDs	600 600mA 800 800mA 1200 1200mA 1800 1800mA	WW Warm White 3000K (80 CRI) NW Neutral White 4000K (70 CRI) CW Cool White 5700K (70 CRI)	SM Surface Mount PM Pendant Mount T Trunnion Mount	5 Type V CD Concentrated Downlight	NONE Leave Blank EBP Emergency Battery Pack	120 120V 208 208V 240 240V 277 277V UNV Universal 120-277V 347 347V 480 480V	NONE Leave Blank DD 0-10V Dimming LLC2 Wireless Controls IMRI Integral Motion Response IMRIC Integral Motion Response Factory Customizable	F1 Single Fuse (120, 277, 347V) F2 Double Fuse (208, 240, 480V) F3 Double Fuse Canadian double pull (208, 240, 347, 480V)	WH White BZ Bronze MGY Medium Grey OC Optional Color Specify optional color or RAL ex: OC-LGP or OC-RAL7024. SC Special Color Must supply color chip. Requires factory quote.

Accessories (ordered separately)

FSIR-100 Handheld programmer
(For use with 'IMRI' and 'IMRIC'
motion response when field
programming is required). If desired,
only one is needed per job.

ES External House Side Shield
(field installed)



2016
Most Innovative
Product of the Year
Best in Category

Prior to ordering, consult specification sheets on philips.com/luminaires for the most current information, notes, and exclusions.

© 2017 Philips Lighting Holding B.V. All rights reserved.
Philips reserves the right to make changes in specifications
and/or to discontinue any product at any time without notice
or obligation and will not be liable for any consequences
resulting from the use of this publication.
philips.com/luminaires

PGc-1602BN 02/17 page 2 of 2



Philips Lighting North America Corporation
200 Franklin Square Drive, Somerset, NJ 08873
Tel. 855-486-2216

Philips Lighting Canada Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3
Tel. 800-668-9008