


# INSTALLATION INSTRUCTIONS

## 300 LINE CYLINDERS – ARM MOUNT RA4,5

IMPORTANT: READ ALL INSTRUCTIONS BEFORE PERFORMING ANY WORK.  
BE SURE ALL POWER IS OFF PRIOR TO INSTALLING LUMINAIRE.

WARNING: LUMINAIRE MUST BE GROUNDED IN ACCORDANCE WITH APPROPRIATE CODES. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY.



1. THREAD (2) TIE RODS INTO FIXTURE. TIGHTEN SNUGLY.
2. SLIDE GASKETS & ARMS ONTO TIE RODS AS SHOWN.
3. PULL LUMINAIRE LEADS THROUGH GASKETS, ARM, POLE, AND POLE BOLSTER PLATE.
4. SQUARE LUMINAIRE & ARM TO POLE AND SECURE TIE RODS WITH 3/8" WASHERS, LOCKWASHERS, & NUTS. TIGHTEN TO 25 FT.-LBS.
5. SPLICE FIELD WIRES TO LUMINAIRE LEADS (INPUT AND GROUNDING). FASTEN FIELD WIRES TO STRAIN RELIEF WIRE TIE.
6. IN LENSED UNITS REMOVE LENS ASSEMBLY IF LAMP INSTALLATION IS REQUIRED. INSTALL LAMP AND REPLACE LENS ASSEMBLY. (TYPICAL LENS ASSEMBLIES ARE SHOWN FOR REFERENCE ONLY)

NOTE: ALL ARM MOUNTED 300 LINE CYLINDERS ARE WET LOCATION RATED. DOWNLIGHT CYLINDERS MAY BE MOUNTED INVERTED IN DAMP LOCATIONS. UPLIGHT CYLINDERS MAY BE MOUNTED INVERTED IN WET LOCATIONS EXCEPT THOSE WITH FORWARD THROW (FT/C) OPTICS.

# PHILIPS

© 2016 Philips Lighting Holding B.V. All rights reserved.

Philips Lighting North America  
Corporation  
200 Franklin Square Drive  
Somerset, NJ 08873, USA

Philips Lighting Canada Ltd.  
281 Hillmount Road,  
Markham ON, Canada L6C 2S3

A817218/443561021520-A