


INSTALLATION INSTRUCTIONS

300 LINE CYLINDERS – CEILING MOUNT




IMPORTANT: READ ALL INSTRUCTIONS BEFORE PERFORMING ANY WORK.
BE SURE ALL POWER IS OFF PRIOR TO INSTALLING LUMINAIRE.

WARNING: LUMINAIRE MUST BE GROUNDED IN ACCORDANCE WITH APPROPRIATE CODES. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY.



H.I.D. AND INCANDESCENT

1. SECURE THE MOUNTING STEM ASSEMBLY (ITEM 1) TO A RECESSED SPLICE BOX (BY OTHERS) USING THE SCREWS THAT COME WITH THE BOX. IF ADDITIONAL SECURITY IS REQUIRED, SCREW OR BOLT THROUGH THE END HOLES IN THE MOUNTING BRACKET INTO STRUCTURAL MEMBERS IN THE CEILING.
2. MAKE ELECTRICAL CONNECTIONS. FIXTURE LINE (BLACK) TO SUPPLY LINE, COMMON (WHITE) TO COMMON AND GROUND TO GROUND.
3. SECURE THE CANOPY (ITEM 2) TO THE MOUNTING BRACKET WITH THE TWO SCREWS SUPPLIED.
4. REMOVE THE TRIM ASSEMBLY FROM THE HOUSING (ITEM 5). THREE TYPICAL TRIMS SHOWN BELOW.
5. ROUTE THE MOUNTING ASSEMBLY PLUG (ITEM 3) THROUGH THE TOP OPENING OF THE HOUSING MAKING SURE IT HANGS TO THE SIDE OF THE SOCKET BRACKET.
6. SCREW THE HOUSING ONTO THE STEM AND LOCK USING THE LOCKING SCREW (ITEM 4).
7. INSERT THE PLUG INTO THE RECEPTACLE FIXED TO THE SOCKET BRACKET.
8. REPLACE THE TRIM AND INSTALL THE LAMP.




THIS REFLECTOR IS FOUND IN BAFFLED OR LENSED TRIMS WHERE E-17 LAMPS ARE SPECIFIED.

PHILIPS

A815651/443561004020-A

INSTALLATION INSTRUCTIONS

300 LINE CYLINDERS – CEILING MOUNT




FORWARD THROW (H.I.D.)

1. SECURE THE MOUNTING STEM ASSEMBLY (ITEM 1) TO A RECESSED SPLICE BOX (BY OTHERS) USING THE SCREWS THAT COME WITH THE BOX.
IF ADDITIONAL SECURITY IS REQUIRED, SCREW OR BOLT THROUGH THE END HOLES IN THE MOUNTING BRACKET INTO STRUCTURAL MEMBERS IN THE CEILING.
2. MAKE ELECTRICAL CONNECTIONS. FIXTURE LINE (BLACK) TO SUPPLY LINE, COMMON (WHITE) TO COMMON AND GROUND TO GROUND.
3. SECURE THE CANOPY (ITEM 2) TO THE MOUNTING BRACKET WITH THE TWO SCREWS SUPPLIED.
4. BACK OUT THE THREE SCREWS THAT SECURE THE LENS ASSEMBLY (ITEM 8) AND REMOVE.
UNSCREW THE TWO SCREWS THAT SECURE THE REFLECTOR ASSEMBLY (ITEM 7) AND SLIDE THIS ASSEMBLY OUT UNTIL THE REFLECTOR PLUG IS ACCESSIBLE. SQUEEZE THE SIDE LOCKING TAB OF THE PLUG TO REMOVE.
UNSCREW THE THREE SCREWS THAT SECURE THE CARRIER ASSEMBLY (ITEM 6) AND REMOVE.
5. ROUTE THE MOUNTING ASSEMBLY PLUG (ITEM 3) THROUGH THE TOP OPENING OF THE HOUSING MAKING SURE IT HANGS TO THE SIDE OF THE RECEPTACLE BRACKET.
6. SCREW THE HOUSING ONTO THE STEM.
7. INSERT THE PLUG INTO THE RECEPTACLE FIXED TO THE RECEPTACLE BRACKET. (THE MOUNTING ASSEMBLY PLUG WILL MATE WITH THE POWER INPUT RECEPTACLE ONLY)
8. REPLACE THE CARRIER ASSEMBLY. INSERT THE REFLECTOR PLUG INTO THE REMAINING RECEPTACLE. CAREFULLY SLIDE THE REFLECTOR ASSEMBLY BACK IN PLACE BEING CAREFULL NOT TO PINCH ANY WIRES. SECURE WITH THE SCREWS PREVIOUSLY REMOVED.
9. INSTALL LAMP AND LENS ASSEMBLY.
10. AIM IN DESIRED DIRECTION AND LOCK HOUSING USING THE LOCKING SCREW (ITEM 4).




INSTALLATION INSTRUCTIONS

300 LINE CYLINDERS – CEILING MOUNT

COMPACT FLUORESCENT



1. SECURE THE MOUNTING STEM ASSEMBLY (ITEM 1) TO A RECESSED SPLICE BOX (BY OTHERS) USING THE SCREWS THAT COME WITH THE BOX.
IF ADDITIONAL SECURITY IS REQUIRED, SCREW OR BOLT THROUGH THE END HOLES IN THE MOUNTING BRACKET INTO STRUCTURAL MEMBERS IN THE CEILING.
2. MAKE ELECTRICAL CONNECTIONS. FIXTURE LINE (BLACK) TO SUPPLY LINE, COMMON (WHITE) TO COMMON AND GROUND TO GROUND.
3. SECURE THE CANOPY (ITEM 2) TO THE MOUNTING BRACKET WITH THE TWO SCREWS SUPPLIED.
4. REMOVE THE TRIM ASSEMBLY FROM THE HOUSING (ITEM 5). BOTH STANDARD TRIMS SHOWN BELOW. (REFLECTOR ASSEMBLY IS REMOVED BY PULLING FROM THE TOP EDGE OF THE LOWER REFLECTOR)
5. ROUTE THE MOUNTING ASSEMBLY PLUG (ITEM 3) THROUGH THE TOP OPENING OF THE HOUSING MAKING SURE IT HANGS TO THE SIDE OF THE SOCKET BRACKET.
6. SCREW THE HOUSING ONTO THE STEM AND LOCK USING THE LOCKING SCREW (ITEM 4).
7. INSERT THE PLUG INTO THE RECEPTACLE FIXED TO THE SOCKET BRACKET.
8. REPLACE THE TRIM AND INSTALL THE LAMP. (MAKE SURE THAT THE THREE REFLECTOR CONNECTING BRACKETS LINE UP WITH THE THREE RETAINING SPRINGS MOUNTED IN THE HOUSING)



PHILIPS

© 2016 Philips Lighting Holding B.V. All rights reserved.

Philips Lighting North America
Corporation
200 Franklin Square Drive
Somerset, NJ 08873, USA

Philips Lighting Canada Ltd.
281 Hillmount Road,
Markham ON, Canada L6C 2S3

A-815651/443561004020-A
3 OF 3