

INSTALLATION INSTRUCTIONS

EXTENDED SPLICE COVER FOR DF7 OR DF12

PHILIPS




IMPORTANT: READ ALL INSTRUCTIONS BEFORE PERFORMING ANY WORK.
BE SURE ALL POWER IS OFF PRIOR TO INSTALLING LUMINAIRES.

NOTE: FOLLOW INSTRUCTIONS SHOWN BELOW BEFORE PROCEEDING TO ANY OTHER MOUNTING INSTRUCTIONS.

TOOLS REQUIRED: 3/16 HEXAGON SOCKET DRIVER WITH A FIVE INCH MINIMUM LENGTH SHAFT AND A #2 PHILLIPS SCREW DRIVER WITH A FIVE INCH MINIMUM LENGTH SHAFT.

1. REMOVE AND DISCARD STANDARD SPLICE COVER AND SCREW FROM DF7 OR DF12 FIXTURE.
2. SECURE BRACKET ASSEMBLY TO CLAMP WITH TWO SELF TAPPING BRACKET SCREWS.
3. PROCEED TO OTHER MOUNTING INSTRUCTIONS SUBSTITUTING THE EXTENDED SPLICE COVER AND SCREW FOR THE STANDARD SPLICE COVER AND SCREW.



PHILIPS