Luxspace Square

Installation instructions

Instructions de montage
Montageanleitung
Montage instruktie

Instrucciones de montaje
Instruções de montagem
Monteringsinstruktioner
Monteringsvejledning


Kokoonpano- ja kiinnitysohjeet
Montaj yönergesi
Instrukcja montazu
Οδηγι ες συναρμολο γ ησης


Szer elési utasítások
Návod k montázi
Návod k montáži
ИН С ТРЦИЯ ПО МОН ТАЖ У


indoor | CE | EN 60598 | IP20 | 50/60Hz | 850°C

		A	B	C	T° K	P max	kg
DN572B	LED12S	300 mm	700 mm	≥3 mm	827	15 W	1,55 kg
					830	12 W	
					840	12 W	
					930	14 W	
	LED20S			≥3 mm	827	20 W	
					830		
					840		
					930		


		A	B	C	T° K	P max	kg
DN572B	LED24S	300 mm	700 mm	≥3 mm	827	24 W	1,55 kg
					830		
					840		
					930		







H	L	□
119 mm	196 mm	214 mm




4411 340 65311
Version Date: 01-07-2015

Data subject to change without notice
Printed in France
www.philips.com/lighting


PHILIPS

FIX PSE-E




220/240V


DALI PSED-E




220/240V

FIX PSU-E







CU3



CU5



THROUGH WIRING




LED Driver 25W 0.3-1A 36V

DO NOT HOT SWAP!

LED heat sink module must not to be disconnected with line POWER ON.


Failure to do so may damage product.




Dali dimming range 1/100%

	XITANIUM 20W LH 0.15-0.5A 48V Is 230V	XITANIUM 20W LH 0.15-0.5A 48V TD/Is 230V	XITANIUM 25W 0.3-1A 36V I 230V	XITANIUM 25W 0.3-1A 36V TD/Is 230V	LED Driver 25W 0.3-1A 36V I 230V
	Electrical Characteristics		Electrical Characteristics		
	∿ ⎓	∿ ⎓	∿ ⎓	∿ ⎓	∿ ⎓
Inom (A)	0.12	0.11	0.2	0.2	0.15
Imax (A)	18	16	8	20	5.2
Tref (µs)	240	220	180	150	50
MCB	Nr. Drivers Max		Nr. Drivers Max		
B-10A	x20	x15	x15	x18	x31
B-16A	x32	x24	x24	x30	x74
C-10A	x33	x24	x24	x31	x74
C-16A	x54	x40	x40	x51	x85


PHILIPS







RIMLESS Housing

DN572B □200 ±2mm







1a



1b




1c




1d

PROTECTION CAP



1e

ZBS260 OCS.







Chiffon doux
Soft cloth
Weiches Tuch
Zacht doekje
Panno morbido
Tejido Suave
Blødt stykke stof
Pehmeä kangas
Miekka sciereczka
Páno macio

EL Version

DN572B EL		
LED12S	LED20S	LED24S
Flux NP		
1110 lm	1900 lm	2200 lm
Flux P		
1110 lm	1900 lm	2200 lm

DN572B EL-CLO		
LED12S	LED20S	LED24S
Flux NP		
888 lm	1520 lm	1760 lm
Flux P		
888 lm	1520 lm	1760 lm





CLO Version


		T° K	Pmax @ t=0h	Pmax @ t=50000h
DN572B	LED12S	827	12 W	15 W
		830	9,6 W	12 W
		840	9,6 W	12 W
		930	11,2W	14 W
	LED20S	827	16 W	20 W
		830		
		840		
		930		
	LED24S	827	19,2 W	24 W
		830		
		840		
		930		

- DO NOT REPROGRAM THE DRIVER
- Constant light Output Option stopped @ 50 000h.


CLO Table		
Step	time (h)	P %
	0	80%
1	3000	81%
2	7000	83%
3	10000	84%
4	13000	85%
5	17000	87%
6	20000	88%
7	23000	89%
8	27000	91%
9	30000	92%
10	33000	93%
11	37000	95%
12	40000	96%
13	43000	97%
14	47000	99%
15	50000	100%

PHILIPS


RIMLESS Version




RIM Accessory




	H	□
DN572B	121 mm	190 mm




DN572B □200 ±2mm




1a




1b




2a



2b



2c



2d

DN572B LED24S 4000K : Groupe de risque 1 suivant la norme IEC 62471:2006 / *Risk group 1 according to IEC 62471:2006*

PHILIPS