



FluxPanel LED

2x4, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse

2x4, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse - 108 lm/W

Philips Day-Brite/Philips CFI FluxPanel LED recessed is a highly versatile luminaire designed to provide smooth lighting gradient on the lens surface and ease of installation. Available for use in recessed, suspended, and surface mount orientation, FluxPanel is ideal for general lighting applications such as open office, schools, healthcare, and retail.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3500K
CRI	80
Mounting	Recessed frange vertaling Surface Suspended

Operating and Electrical	
Luminaire Input Watts	38
Voltages	120/277/347/UNIV V

Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular

Initial Performance (IEC Compliant)	
Luminaire Lumens	4200
Efficacy	108 lm/W

Product Data	
Order product name	2x4, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse
Commercial Code	2FXP42B835-4-DS-UNV-DIM
Order code	2FXP42B835-4-DS-UNV-DIM
Catalog Number Description	2x4, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse
Service / Spec Smart	Service Smart (2 Days) North America
Material Nr. (12NC)	CFI70000735